Table of Contents

17.08.15 - Idaho Minimum Safety Standards and Practices for Logging --Commonly Used Logging Terms

000. Legal Authority.	2
001. Title And Scope.	2
002. Written Interpretations.	2
003. Administrative Appeals.	
004 008. (Reserved).	2
009. Definitions.	2
010. Definitions.	2
011 999. (Reserved).	6

IDAPA 17 TITLE 08 CHAPTER 15

17.08.15 - IDAHO MINIMUM SAFETY STANDARDS AND PRACTICES FOR LOGGING -- COMMONLY USED LOGGING TERMS

000. LEGAL AUTHORITY.

Pursuant to the provisions of Section 72-508, Idaho Code, the Industrial Commission has the authority to promulgate and adopt reasonable rules for effecting the purposes of the Workers' Compensation Act. (7-1-97)

001. TITLE AND SCOPE.

These rules shall be cited as IDAPA 17.08.15, "Idaho Minimum Safety Standards and Practices for Logging --Commonly Used Logging Terms," and shall be applicable to the logging industry in the state of Idaho. (7-1-97)

002. WRITTEN INTERPRETATIONS.

There are no written statements which pertain to the interpretation of these rules. (7-1-97)

003. ADMINISTRATIVE APPEALS.

There are no provisions for administrative appeal of these rules. The procedure for appeals in safety matters is prescribed by Sections 72-714 and 72-718 through 72-722, Idaho Code. (7-1-97)

004. -- 008. (RESERVED).

009. **DEFINITIONS.**

For additional definitions refer to IDAPA 17.08.01, "Idaho Minimum Safety Standards and Practices for Logging --General Provisions," Section 007. (7-1-97)

010. **DEFINITIONS.**

01. A-Frame. A structure made of the independent columns (of wood or steel) fastened together at the top and separated a reasonable width at the bottom to stabilize the unit from tipping sideways. (7-1-97)

02. Arch. A piece of equipment attached to rear of vehicle, used for raising one end of logs to facilitate skidding. (7-1-97)

03. Back Cut. The final falling cut. (7-1-97)

04. Barber Chair. Slab portion of tree remaining on the stump above the back cut due to improper (7-1-97)

05. Bell or Cup Hook With Spike. A hook consisting of a cylindrical cup from whose center there (7-1-97)

06. Bight. The loop of a line, the ends being "gast" elsewhere, or the angle formed by a line running (7-1-97)

- **07. Binder**. Chain, cable, or steel strap used for binding loads of logs. (7-1-97)
- **08.** Blasting Cap. A metal shell containing a detonating compound. (7-1-97)

09. Brailling. One (1) section of flat log raft enclosed by boom sticks. To place logs end to end in a long flat raft or boom. (7-1-97)

10. Brow Log. A log placed parallel to any roadway at a landing or dump to protect vehicles while loading or unloading. (7-1-97)

11.Bullbuck. The supervisor over cutting crew.(7-1-97)

IDAPA 17.08.15 - Minimum Safety Standards & Practices for Logging - Commonly Used Logging Terms

12. the base.	Buckle Guy Line. Line used to stiffen or support a tree, pole, or structure between the top	p guys and (7-1-97)
13.	Bunk. The cross support for logs on a logging car or truck.	(7-1-97)
14.	Butt Hook. Hook at end of haul-in line for attaching chokers to line.	(7-1-97)
15.	Butt Rigging. Arrangement at end of main line for attaching chokers.	(7-1-97)
16.	Capped Fuse. A piece of fuse to which a blasting cap has been crimped.	(7-1-97)
17. Carriage Logging. A type of high lead logging using gravity, haul back, or, remote c carriages to yard logs. (Bullet carriage is one type). (7		
18.	Cat Road. A tractor road.	(7-1-97)
19. on skid road.	Chaser. The member of the yarding crew who unhooks the logs at the landing or fights	s hang-ups (7-1-97)
20.	Chipper. A machine which cuts materials into chips.	(7-1-97)
21.	Chock (Bunk Block-Cheese Block). A wedge that prevents logs from rolling off the bur	nks. (7-1-97)
22.	Cheater. Extension to bunk stakes.	(7-1-97)
23.	Choker. A wire rope with special attachments put around log near the end for hauling or	lifting. (7-1-97)
24.	Cold Deck. Any pile of logs which is yarded and left for future removal.	(7-1-97)
24. 25.	Cold Deck. Any pile of logs which is yarded and left for future removal.Cold Shut. A link for joining two (2) chains, the link being closed cold with a hammer, removed and the statement of the	. ,
25. 26.		not a weld. (7-1-97)
25. 26. with the leading 27.	Cold Shut . A link for joining two (2) chains, the link being closed cold with a hammer, r Connecting Wires . Means those wires that connect the leg wire of one (1) electric blast	not a weld. (7-1-97) ting cap or (7-1-97)
25. 26. with the leading 27.	 Cold Shut. A link for joining two (2) chains, the link being closed cold with a hammer, r Connecting Wires. Means those wires that connect the leg wire of one (1) electric blast wires, when blasting in series. Crotch Line. Two (2) short lines attached to hoisting line by means of a ring or shackle, 	not a weld. (7-1-97) ting cap or (7-1-97) , the lower
25. 26. with the leading 27. ends being attac 28. 29.	 Cold Shut. A link for joining two (2) chains, the link being closed cold with a hammer, r Connecting Wires. Means those wires that connect the leg wire of one (1) electric blast wires, when blasting in series. Crotch Line. Two (2) short lines attached to hoisting line by means of a ring or shackle, hed to loading hooks and used for loading or unloading. 	not a weld. (7-1-97) ting cap or (7-1-97) , the lower (7-1-97) (7-1-97)
25. 26. with the leading 27. ends being attac 28. 29.	 Cold Shut. A link for joining two (2) chains, the link being closed cold with a hammer, r Connecting Wires. Means those wires that connect the leg wire of one (1) electric blast wires, when blasting in series. Crotch Line. Two (2) short lines attached to hoisting line by means of a ring or shackle, thed to loading hooks and used for loading or unloading. Cutter. A term used to designate faller or bucker. D or Strap Socket. A socket with a closed loop and arranged to be attached to the end of the end	not a weld. (7-1-97) ting cap or (7-1-97) , the lower (7-1-97) (7-1-97) of a line. It
25. 26. with the leading 27. ends being attac 28. 29. is used in place	 Cold Shut. A link for joining two (2) chains, the link being closed cold with a hammer, r Connecting Wires. Means those wires that connect the leg wire of one (1) electric blast wires, when blasting in series. Crotch Line. Two (2) short lines attached to hoisting line by means of a ring or shackle, thed to loading hooks and used for loading or unloading. Cutter. A term used to designate faller or bucker. D or Strap Socket. A socket with a closed loop and arranged to be attached to the end of a spliced eye. 	not a weld. (7-1-97) ting cap or (7-1-97) , the lower (7-1-97) (7-1-97) of a line. It (7-1-97)
25. 26. with the leading 27. ends being attac 28. 29. is used in place 30.	 Cold Shut. A link for joining two (2) chains, the link being closed cold with a hammer, r Connecting Wires. Means those wires that connect the leg wire of one (1) electric blast wires, when blasting in series. Crotch Line. Two (2) short lines attached to hoisting line by means of a ring or shackle, thed to loading hooks and used for loading or unloading. Cutter. A term used to designate faller or bucker. D or Strap Socket. A socket with a closed loop and arranged to be attached to the end of a spliced eye. Dead Man. Buried log or other object used as an anchor. 	not a weld. (7-1-97) ting cap or (7-1-97) , the lower (7-1-97) (7-1-97) of a line. It (7-1-97) (7-1-97) (7-1-97)
25. 26. with the leading 27. ends being attac 28. 29. is used in place 30. 31. 32. 33.	 Cold Shut. A link for joining two (2) chains, the link being closed cold with a hammer, r Connecting Wires. Means those wires that connect the leg wire of one (1) electric blast wires, when blasting in series. Crotch Line. Two (2) short lines attached to hoisting line by means of a ring or shackle, the to loading hooks and used for loading or unloading. Cutter. A term used to designate faller or bucker. D or Strap Socket. A socket with a closed loop and arranged to be attached to the end of a spliced eye. Dead Man. Buried log or other object used as an anchor. Detonator. Means blasting cap, electric blasting cap, or delay electric blasting cap. 	not a weld. (7-1-97) ting cap or (7-1-97) the lower (7-1-97) (7-1-97) of a line. It (7-1-97) (7-1-97) (7-1-97) (7-1-97) (7-1-97)

IDAHO ADMINISTRATIVE CODE Industrial Commission

IDAPA 17.08.15 - Minimum Safety Standards & Practices for Logging - Commonly Used Logging Terms

35. Explosive. Any chemical compound or mechanical mixture that is commonly used that contains any oxidizing and combustible units, or other ingredients, in such proportions, quantities or packing that an ignition by fire, friction concussion, percussion, or detonator of any part of the compound or mixture may cause such a sudden generation of highly heated gases that the resultant gaseous pressures are capable of producing destructive effects on contiguous objects or destroying life or limb. (7-1-97)

36. Fair Lead. A combination of a pair of sheaves or roller set transversely or vertically in a unit in front of another pair of sheaves to guide a line coming from any direction and leading it properly to a drum. (7-1-97)

37.	Gin Pole. A raised pole properly guyed and used to support lines and blocks.	(7-1-97)
38.	Grapple. A device attached to hoisting line for mechanically handling logs.	(7-1-97)
39.	Gut Wrapper. Intermediate binder for an individual tier of logs.	(7-1-97)
40.	Guy Lines. The lines used to stay or support spar trees, booms, etc.	(7-1-97)
41. Used to return the set of t	Haul Back . A small wire line traveling between the power skidder and a pulley set near ne main cable with tongs, chokers, or hooks to the next log.	the logs. (7-1-97)
42.	Heel Block. The block heel of boom.	(7-1-97)
43.	Heel Boom. A type of loading boom where one end of the log is pulled up against the boo	om. (7-1-97)
44. to the place of lo	Hook Tender, Hooker. The worker who supervises the method of moving the logs from toading.	he woods (7-1-97)
45.	Hazard. Any condition or circumstance which may cause an accident or injury.	(7-1-97)
46.	Jaggers. Any projecting broken strand of cable.	(7-1-97)
47.	Jammer. A machine used for handling logs.	(7-1-97)
48.	Jill Poke. A projecting object out of its normal position.	(7-1-97)
49.	Knob . A metal ferrule arranged to be attached to the end of a line, used in place of a splic	ed eye. (7-1-97)
50. unloading.	Landing, Rollway. Any place where logs are placed, after being yarded, awaiting lo	oading or (7-1-97)
51. direction.	Lang Lay Rope. A wire rope, in which the wires in the strands of the rope are laid in	the same (7-1-97)
52. generating devise	Leading Wires . Those wires between the "connecting wires" or "leg wires" and a se or an approved type blasting battery in series blasting.	portable (7-1-97)
53.	Leaners. A live or dead leaning tree.	(7-1-97)
54.	Loading Boom. Any structure projecting from a pivot point to guide a log when lifted.	(7-1-97)
55.	Log Stacker. A machine with lift forks used to handle logs.	(7-1-97)
56.	Magazine. Any building or other structure used exclusively for the storage of explosives.	(7-1-97)

IDAHO ADMINISTRATIVE CODEIDAPA 17.08.15 - Minimum Safety Standards & PracticesIndustrial Commissionfor Logging - Commonly Used Logging Terms

	57	Operation (Show Woods Lowent) Any place where leaving is heing done	(7, 1, 07)	
	57.	Operation (Show Woods Layout) . Any place where logging is being done.	(7-1-97)	
	58.	Mainline. A cable which pulls logs or trees to loading.	(7-1-97)	
rest.	59.	Pan (Skidding Pan). A solid piece of metal placed behind a tractor on which one (1) en	nd of logs (7-1-97)	
	60.	Peeling Bar or Spud. A tool for removing bark from trees or logs.	(7-1-97)	
	61.	Pike, Pole. A long pole whose end is shod with a sharp pointed steel spike, point, and/or	hook. (7-1-97)	
62. Portable Spar or Tower. An engineered structure designed to be used in a manner similar to which a wooden spar tree would be used. (7-1-97)				
	63.	Powder . Any explosive other than the detonating agent.	(7-1-97)	
	64.	Primer. A cartridge of explosive with a detonator inserted there in.	(7-1-97)	
	65.	Reach. An adjustable beam between trailer and motorized logging vehicle.	(7-1-97)	
yarder.	66.	Receding Line. The line on which a skidder or slack-line comparable to the haul back	line on a (7-1-97)	
	67.	Reload. Any area where logs are dumped and reloaded.	(7-1-97)	
	68.	Running Line. Any line which moves.	(7-1-97)	
	69.	Sail Guy. A guy which holds the outer end of a boom.	(7-1-97)	
	70. Sail Block. A block hung inverted on the sail guy to hold the tong block in proper position. (7-1-97)			
	71.	Schoolmarm. A crotched tree consisting chiefly of two (2) trunks.	(7-1-97)	
	72.	Skids. Any group of timbers spaced a short distance apart on which the logs are placed.	(7-1-97)	
sufficie	73. nt to fall,	Side, Show, Chance . That unit of a logging operation, including men and equipme buck, and load a given area ready for transportation of the logs to the mill.	nt that is (7-1-97)	
74. Side Winders. A piece of log, brush, or limb thrown up or sideways during skidding operation. A tree knocked down by another in falling. (7-1-97)				
the oper	75. rator.	Signalman, Whistle Punk. The authorized worker who transfers signals from a given le	ocation to (7-1-97)	
	76.	Skidding. Movement of logs on the ground.	(7-1-97)	
bullet tr	77. cavels.	Skyline. The supporting line on various types of logging systems on which carriage,	block, or (7-1-97)	
	78.	Slack Line. A form of skyline where skyline is spooled on drum and can be raised or low	vered. (7-1-97)	
inadequ	79. 1ate.	Slack Puller. Any device used to increase the movement of a line when its own	weight is (7-1-97)	

IDAHO ADMINISTRATIVE CODE Industrial Commission

IDAPA 17.08.15 - Minimum Safety Standards & Practices for Logging - Commonly Used Logging Terms

80.	Snags. Any dead standing trees.	(7-1-97)
81. looping the line	Snubbing . A method of retarding or controlling the movement of logs or machine by around a stationary object.	means of (7-1-97)
82. ground level.	Spring Board. A board with an iron tip used by fallers to stand on when they must stand	above the (7-1-97)
83.	Strap. Any short piece of line with an eye or "D" in each end.	(7-1-97)
84.	Strawline. A small line used for miscellaneous purposes.	(7-1-97)
85.	Strip. A definite location of timber allocated to a cutting crew.	(7-1-97)
86.	Sweeper. Unexpected and controlled lateral movement of log, tree, etc. during skidding o	perations. (7-1-97)
87.	Swamp. The falling or clearing of limbs and brush around or along a specific place.	(7-1-97)
88.	Tag Line. A line used to control movement during loading, unloading, or skidding operate	tions. (7-1-97)
89.	Tail Hold. Any anchor used for making fast any line.	(7-1-97)
90.	Tell Tale. A devise used to serve as a warning for overhead hazards.	(7-1-97)
91.	Tight Line. When power is exerted on both mainline and haul back at the same time.	(7-1-97)
92.	Tongs. A hooking device used to lift or skid logs.	(7-1-97)
93.	Transfer. Changing of a load of logs in a unit from one means of transportation to anothe	er. (7-1-97)
94.	Tree Plates. Steel protectors spiked around a tree to prevent the lines from cutting into th	e trees. (7-1-97)
95.	Undercut. A notch cut in the tree to guide and control the tree in falling.	(7-1-97)
96.	Windfall. A tree felled by the wind or other natural causes.	(7-1-97)
97.	Widow Maker. A loose limb, top, or piece of bark which may fall on a logger working b	eneath it. (7-1-97)
98. shipping point.	Yarding. Movement of logs or trees from the place they are felled (bucked) to a central l	oading or (7-1-97)
011 999.	(RESERVED)	

011. -- 999. (RESERVED).

Subject Index

D Definitions, IDAPA 17.08.15, Idaho Minimum Safety Standards & Practice For Logging -- Commonly Used Logging Terms 2