

# Table of Contents

## 39.03.25 - RULES GOVERNING LIGHTS ON SNOW REMOVAL EQUIPMENT

000. LEGAL AUTHORITY. ....	2
001. TITLE AND SCOPE. ....	2
002. -- 009. (RESERVED). ....	2
010. DEFINITIONS. ....	2
011. -- 099. (RESERVED). ....	2
100. LIGHTING STANDARDS. ....	2
101. -- 999. (RESERVED). ....	2

**39.03.25 - RULES GOVERNING LIGHTS ON SNOW REMOVAL EQUIPMENT**

**000. LEGAL AUTHORITY.**

This rule is adopted under the authority of Sections 40-312 and 49-929, Idaho Code. (9-4-91)

**001. TITLE AND SCOPE.**

This rule specifies and standardizes the lighting systems on snow removal equipment. These specifications and standards supersede Administrative Policy A-05-26 (dated 06-23-82) and Board Policy B-05-26 (dated 6-16-82). (9-4-91)

**002. -- 009. (RESERVED).**

**010. DEFINITIONS.**

Snow Removal Equipment - Any private or publicly-owned vehicle classified as a motorized vehicle as defined in Section 49-123, Idaho Code, that has been equipped with snow removal equipment and is being used for snow removal on any public highway. (9-4-91)

**011. -- 099. (RESERVED).**

**100. LIGHTING STANDARDS.**

01. Headlamps, Turn Signals, and Flashing Lights. Headlamps, turn signals and flashing lights shall be mounted on snow removal equipment at sufficient height to clear all snow removal apparatus. (9-4-91)

02. Visibility Requirements. Flashing identification lights on snow removal equipment must be amber colored, and mounted on the cab or truck bed. They shall be mounted so as to be visible from the front and rear regardless of vehicle configuration, for example, when the truck bed is raised. Flashing lights shall be visible from a distance of not less than one thousand (1,000) feet in normal sunlight, and not less than two thousand five hundred (2,500) feet under average visibility conditions at night. (9-4-91)

03. Lights to Meet Idaho Code Requirements. Tail lamps, stop lamps and clearance lamps on snow removal equipment must meet standards specified in appropriate sections of the Idaho Code. (9-4-91)

**101. -- 999. (RESERVED).**