

# Table of Contents

## 39.03.17 - RULES GOVERNING OVERSIZE PERMITS FOR MANUFACTURED HOMES, MODULAR BUILDINGS, AND OFFICE TRAILERS

000. LEGAL AUTHORITY. ....	2
001. TITLE AND SCOPE. ....	2
002. -- 009. (RESERVED). ....	2
010. DEFINITIONS. ....	2
011. -- 099. (RESERVED). ....	2
100. REGISTRATION AND LICENSING REQUIREMENTS. ....	2
101. INSURANCE REQUIREMENTS. ....	2
102. -- 199. (RESERVED). ....	2
200. MANUFACTURED HOMES AND OFFICE TRAILERS BEING TOWED. ....	2
201. VEHICLES FOR TOWING MANUFACTURED HOMES AND OFFICE TRAILERS. ....	3
202. -- 299. (RESERVED). ....	4
300. MANUFACTURED HOME, MODULAR BUILDING, OR OFFICES BEING HAULED. ....	4
301. HAULING EQUIPMENT FOR A MANUFACTURED HOME, MODULAR BUILDING OR OFFICE. ....	4
302. -- 399. (RESERVED). ....	4
400. GENERAL PROVISIONS. ....	4
401. -- 999. (RESERVED). ....	5

**IDAPA 39  
TITLE 03  
Chapter 17**

**39.03.17 - RULES GOVERNING OVERSIZE PERMITS FOR  
MANUFACTURED HOMES, MODULAR BUILDINGS, AND OFFICE TRAILERS**

**000. LEGAL AUTHORITY.**

This rule, governing the movement of manufactured homes, modular buildings, and office trailers in excess of the sizes allowed by Section 49-1010, Idaho Code, is adopted under the authority of Sections 40-312 and 49-1004, Idaho Code. (8-25-94)

**001. TITLE AND SCOPE.**

This rule states the regulations for special permits issued for the movement of manufactured homes, modular buildings and office trailers. (8-25-94)

**002. -- 009. (RESERVED).**

**010. DEFINITIONS.**

Refer to Rule 39.03.01 for definitions of the terms used in this rule. (10-2-89)

**011. -- 099. (RESERVED).**

**100. REGISTRATION AND LICENSING REQUIREMENTS.**

All manufactured homes and office trailers moved on any public highway are required to be licensed. New and resale units shall carry license plates provided by the dealer or transporter. Other units shall be licensed by the owner. The manufactured home and office trailer registration and general property tax receipt shall be made available for inspection upon demand of any enforcement officer. (8-25-94)

**101. INSURANCE REQUIREMENTS.**

The permittee or the driver of the vehicle towing overwidth manufactured homes and office trailers shall be required to carry evidence of general liability insurance in the permitted vehicle written by a company licensed in Idaho showing coverage in the minimum amounts of five hundred thousand dollars (\$500,000) when hauling permittee's own manufactured home. When hauling for hire permittee must carry a minimum amount of seven hundred and fifty thousand dollars (\$750,000) insurance coverage, and have proper authority. (1-1-97)T

**102. -- 199. (RESERVED).**

**200. MANUFACTURED HOMES AND OFFICE TRAILERS BEING TOWED.**

01. Connection Device. A ball hitch coupler. (10-2-89)

02. Length. Not in excess of eighty (80) feet including tongue. (10-2-89)

03. Width. Shall be limited to a maximum of sixteen (16) feet at the base and shall not exceed eighteen (18) feet overall width including the eaves. (1-1-97)T

\*\* Determination of manufactured home or office trailer width shall be exclusive of such appurtenances as clearance lights, door handles, window fasteners, door and window trim, moldings and load securement devices up to but not in excess of three (3) inches on each side of load. (1-1-97)T

04. Eaves. The eaves may extend up to sixteen (16) inches as long as the eighteen (18) feet maximum overall width limitation is not exceeded. (1-1-97)T

05. Weight. The maximum allowable load for any vehicle tire operated on any public highway shall be in accordance with Code of Federal Regulations, Title 24, Chapter 20, Office of Assistant Secretary for Housing - Federal Housing Commissioner, Department of Housing and Urban Development, Part 3280, Subpart J, (CFR Title 24). (1-1-97)T

06. Running Gear Assembly - General. The entire system (frame, drawbar, and coupling mechanism, running gear assembly including brake systems, axles and lights) shall be in accordance with CFR Title 24, for the year the manufactured home was built. In addition thereto, all tires used in transportation of manufactured homes under this category shall be in accordance with Federal Motor Carrier Safety Regulations, part 393. (1-1-97)T

07. Construction. Construction shall be in accordance with CFR Title 24, for the year the manufactured home was built. (1-1-97)T

08. Axles. All axles shall be in accordance with CFR Title 24, for the year the manufactured home was built, except that sixteen (16) foot wide (at the base) manufactured homes shall be required to have a minimum of four (4) axles. (1-1-97)T

09. Brakes. Brakes shall be in accordance with CFR Title 24, for the year the manufactured home was built, except that sixteen (16) foot wide (at the base) manufactured homes shall be required to have brakes on a minimum of three (3) axles. (1-1-97)T

10. Lights. The unit shall have stop lights, turn signals and tail lights that meet the requirements of Federal Motor Carrier Safety Regulations, part 393 (1-1-97)T

11. Safety Chains. Two (2) safety chains shall be used, one (1) each on right and left sides of, but separate from, the coupling mechanism connecting the tow vehicle and the manufactured home while in transit. Chain shall be three-eighths (3/8) inch diameter steel. Chains shall be strongly fastened at each end to connect the tow vehicle and manufactured home and assure that in the event of a coupling failure the manufactured home will track behind the tow vehicle. (1-1-97)T

**201. VEHICLES FOR TOWING MANUFACTURED HOMES AND OFFICE TRAILERS.**

01. Towing Vehicle. Tow vehicles for manufactured homes and office trailers shall comply with the following minimum requirements:

<b>Manufactured Homes and Office Trailers Width</b>	<b>Tire Width</b>	<b>Drive Axle Tire Rating</b>	<b>Min. Unladen Weight</b>	<b>Rear Axle Rating</b>
Over 8' to 10'	7.00"	6 Ply	6,000#	None
Over 10'to 12'	8.00"	8 Ply	8,000#	15,000#
Over 12'	8.25"	10 Ply	12,000#	15,000#

(1-1-97)T

02. Brakes. Shall be in accordance with Federal Motor Carrier Safety Regulations part 393. (8-25-94)

03. Rear Axle. Towing vehicle shall have a minimum of a single axle with dual mounted tires. (8-25-94)

04. Hitch Assembly. Shall meet the requirements of Federal Motor Carrier Safety Regulations, part 393. (8-25-94)

05. Horsepower Requirement. When towing a manufactured home or office trailer a minimum speed of twenty-five (25) mph must be maintained. (1-1-97)T

06. Two-Way Radio. (1-1-97)T

a. On all movements requiring an escort vehicle, both the towing unit and the escort vehicle(s) shall be equipped with two-way radio equipment, licensed under Federal Communications Commission regulations

adequate to provide reliable voice communication between the drivers thereof at all times during the movement of the escorted load. Transmitting and receiving capabilities of the radio equipment used shall be adequate to provide the required communication over a minimum distance of one-half (1/2) mile separation under conditions normally encountered along the proposed route. (1-1-97)T

b. Radio communication shall be open and monitored between escort vehicle(s) and oversize load at all times during movement. (1-1-97)T

07. Operator Requirements. Operators of vehicles towing manufactured homes, modular buildings and office trailers over ten (10) feet wide at the base shall have a class A or B Commercial Driver's License (CDL) as appropriate. (1-1-97)T

08. Speed Limit Requirements. Vehicles towing manufactured homes, modular buildings and offices, shall be limited to a maximum of sixty (60) miles per hour. (1-1-97)T

**202. -- 299. (RESERVED).**

**300. MANUFACTURED HOME, MODULAR BUILDING, OR OFFICES BEING HAULED.**

01. Length. Not in excess of eighty (80) feet. (10-2-89)

02. Width. Not in excess of sixteen (16) feet at the base and eighteen (18) feet overall. (1-1-97)T

03. Eaves. The eaves may extend up to sixteen (16) inches as long as the eighteen (18) foot maximum overall width limitation is not exceeded. (1-1-97)T

**301. HAULING EQUIPMENT FOR A MANUFACTURED HOME, MODULAR BUILDING OR OFFICE.**

01. Hauling Equipment. Vehicles used to haul manufactured homes, modular buildings and office trailers shall be combinations designed to meet the requirements of Federal Motor Carrier Safety Regulations for vehicles engaged in interstate commerce. Such vehicles shall be of structural capacity to safely accommodate the loading at all times. (8-25-94)

02. Lights. The unit shall have stop lights, turn signals and tail lights that meet the requirements of Federal Motor Carrier Safety Regulations, part 393. (8-25-94)

03. Securing Loads. A minimum of four (4) steel, three fourths (3/4) inch diameter bolts will be used to directly connect the main support members of the modular building, manufactured home or office trailer to the support frame of moving equipment. Two (2) bolts each shall be located not less than twelve (12) feet from the forward and rear ends of the modular building, manufactured home or office trailer. Each of the four (4) bolts shall be at least four (4) feet apart. Equivalent methods of fastening, such as chains or binders, may be used as alternatives. (8-25-94)

**302. -- 399. (RESERVED).**

**400. GENERAL PROVISIONS.**

01. Paneling of Open Sides of Multi-Section Modular Buildings, Manufactured Homes or Office Trailers. Shall be rigid material, or six (6) mil plastic sheathing (or stronger) backed by a grillwork to prevent billowing and fully enclose open sides of section in transit. (1-1-97)T

02. Interior Loading. If the manufactured home or office trailer is to transport furnishings or other loose objects they shall be secured in position for safe travel. (8-25-94)

03. Construction. Modular buildings shall be constructed in accordance with the Uniform Building Code as applies to design and construction requirements that will affect overall structural strength and roadability.

Manufactured homes and offices shall be constructed in accordance with Federal HUD Manufactured Home Construction and Safety Standards. (8-25-94)

04. Oversize Manufactured Homes or Office Trailers. Oversize manufactured Homes or Office Trailers must be transported under authority of the rule. Rule 39.03.16 does not apply to the transport of Manufactured Homes or Office Trailers. (8-25-94)

05. Manufactured Homes and Office Trailers. This rule applies only to Manufactured Homes and Office Trailers and does not apply to individual components utilized in the manufacturing of Manufactured Homes (ie., frames, suspension, ect.). Permits may be issued to authorize transport of components for Manufactured Homes or Office Trailers under Rule 39.03.16. (8-25-94)

06. Signs. All manufactured homes, modular buildings and office trailers whether hauled or towed shall be required to display an oversize load sign, even if no escort vehicles are required. The sign shall meet the following dimensions: eighteen (18) inches high by seven (7) feet wide, letter height ten (10) inches, letter type standard series C, stroke width one and five-eighths (1 5/8) inch, black letters on yellow background. (1-1-97)T

07. Warning Flags. All manufactured homes, modular buildings and office trailers whether hauled or towed shall be required to display flags on all four corners. The flags may be red or fluorescent orange. (1-1-97)T

08. Warning Lights. All manufactured homes, modular buildings and offices whether hauled or towed shall be required to display two (2) flashing or rotating amber lights (visible from five hundred (500) ft.) on the back of the manufactured home, modular building or office. (1-1-97)T

09. Permits. Annual permits will allow travel on the following routes at the following dimensions:

Route	Base Width	Overall Width	Height	Overall Length
Red		12' 6"	15' 6"	110'
Black	14'	18'	15' 6"	110'
Double Black	16'	18'	15' 6"	110'

The double black routes are the interstate and 4 lane highways

\*\*The routes referred to above are on the Escort Vehicle and Travel Time Requirements Map.

\*\*When exceeding the above maximum dimensions allowed for a route, movement will be allowed only by single trip permit.

\*\*Manufactured homes, modular buildings and offices exceeding sixteen (16) feet overall width being towed on their own axles on two lane highways, will be required to submit for approval a traffic control plan, that lists at a minimum the following information: date of move, routes of travel, turnouts for traffic relief, and dimensions of load. (1-1-97)T

**401. -- 999. (RESERVED).**