

# *Table of Contents*

---

## **39.03.06 - RULES GOVERNING ALLOWABLE VEHICLE SIZE**

000. AUTHORITY.....	2
001. TITLE AND SCOPE.....	2
002. -- 009. (RESERVED).....	2
010. DEFINITIONS.....	2
011. -- 099. (RESERVED).....	2
100. ALLOWABLE TOLERANCE, LEGAL OR PERMITTED SIZE LIMITS.....	2
101. -- 199. (RESERVED).....	2
200. DROMEDARY TRACTORS.....	2
201. -- 299. (RESERVED).....	2
300. LOAD OVERHANG.....	2
301. -- 999. (RESERVED).....	2

**IDAPA 39  
TITLE 03  
CHAPTER 06**

**39.03.06 - RULES GOVERNING ALLOWABLE VEHICLE SIZE**

**000. AUTHORITY.**

This rule is adopted under authority of Sections 40-312(1) and 49-1011, Idaho Code. (10-2-89)

**001. TITLE AND SCOPE.**

This rule is promulgated to define and regulate the size of vehicles not specifically addressed in Section 49-1010 of the Idaho Code or to authorize vehicle sizes in excess of those specified in Section 49-1010, Idaho Code, in order to comply with federal requirements. (10-2-89)

**002. -- 009. (RESERVED).**

**010. DEFINITIONS.**

Refer to Rule 39.03.01 for definitions of the terms used in this rule. (10-2-89)

**011. -- 099. (RESERVED).**

**100. ALLOWABLE TOLERANCE, LEGAL OR PERMITTED SIZE LIMITS.**

**01. Determination Of Vehicular Dimensions.** Determination of vehicular length and/or width as defined by Idaho Code or by Board regulation shall be exclusive of those external devices or appurtenances whose function is related to safe and efficient operation. (10-2-89)

**02. Appurtenances.** Rearview mirrors, turn signal lamps, splash and spray suppressant devices and load induced tire bulge shall be excluded from the calculation of allowable width. Front mounted refrigeration units, energy conservation devices, bolsters, mechanical fastening devices, hydraulic lift gates, external front mounted side curtain rollers, and other noncargo carrying appurtenances or devices shall be excluded from a determination of allowable length. (1-03-92)

**03. Other Appurtenances.** Other appurtenances not listed above may not extend beyond three (3) inches on each side or end of a vehicle or load. Other appurtenances may include, but shall not be limited to, clearance lights, door handles, handholds, window fasteners, door and window trim, moldings, and load securement devices. (10-2-89)

**101. -- 199. (RESERVED).**

**200. DROMEDARY TRACTORS.**

A truck tractor containing a dromedary box, deck or plate in legal operation on or before December 1, 1982, shall be authorized to continue to operate, notwithstanding its cargo carrying capacity, throughout its useful life. Proof of such legal operation on December 1, 1982, shall rest upon the operator of the equipment. (12-26-90)

**201. -- 299. (RESERVED).**

**300. LOAD OVERHANG.**

The overhang or extension of a load shall not extend: (9-14-92)

**01. Front.** More than four (4) feet beyond the front of a vehicle other than an automobile transporter or a boat transporter. (4-24-92)

**02. Rear.** More than fifteen (15) feet beyond the last axle of a vehicle other than an automobile transporter or a boat transporter. (4-24-92)

**03. Right Side.** More than six (6) inches outside the right fender of a passenger vehicle. (4-24-92)

**04. Left Side.** Outside the left fender of a passenger vehicle. (4-24-92)

**05. Auto Or Boat Transporter.** More than seven (7) feet front and rear combined length of an automobile transporter or boat transporter. (4-24-92)

**301. -- 999. (RESERVED).**

# ***Subject Index***

## **A**

Allowable Tolerance, Legal Or  
Permitted Size Limits, Allowable  
Vehicle Size 2  
Appurtenances, Determination Of  
Allowable Length & Width,  
Allowable Vehicle Size 2  
Auto Or Boat Transporter, Load  
Overhang, Allowable Vehicle  
Size 2

## **D**

Definitions, IDAPA 39.03.06, Rules  
Governing Allowable Vehicle  
Size 2  
Determination Of Vehicular  
Dimensions, Allowable Vehicle  
Size 2  
Dromedary Tractors, Allowable Vehicle  
Size 2

## **L**

Left Side, Load Overhang, Allowable  
Vehicle Size 2  
Load Overhang, Allowable Vehicle  
Size 2

## **R**

Right Side, Load Overhang, Allowable  
Vehicle Size 2