

Table of Contents

39.03.12 - Rules Governing Safety Requirements of Overlegal Permits

000. Legal Authority.	2
001. Title And Scope.	2
002. -- 009. (Reserved).	2
010. Definitions.	2
011. -- 099. (Reserved).	2
100. Lighting Requirements For Oversize Vehicles And/Or Loads Traveling After Dark.	2
101. -- 199. (Reserved).	3
200. Flagging Requirements For Oversize Vehicles And/Or Loads.	3
201.-- 299. (Reserved).	3
300. Signing Requirements Of Oversize Vehicles And/Or Loads.	3
301. -- 399. (Reserved).	3
400. Pilot/Escort Vehicles.	3
401. -- 499. (Reserved).	3
500. Pilot/Escort Vehicle Sign Requirements.	3
501. -- 599. (Reserved).	4
600. Pilot/Escort Vehicle Lighting Requirements.	4
601. -- 699. (Reserved).	4
700. Pilot/Escort Vehicle Equipment.	4
701. -- 799. (Reserved).	4
800. Pilot/Escort Vehicle Placement.	4
801. -- 899. (Reserved).	5
900. Convoy Of Overlegal Loads.	5
901. -- 949. (Reserved).	5
950. Pilot/Escort Vehicle And Travel Time Requirements Map.	5
951. -- 999. (Reserved).	5

**IDAPA 39
TITLE 03
CHAPTER 12**

39.03.12 - RULES GOVERNING SAFETY REQUIREMENTS OF OVERLEGAL PERMITS

000. LEGAL AUTHORITY.

This rule, governing the movement of vehicles or loads which are in excess of the sizes or weights allowed by Sections 49-940, 49-1001, 49-1002 or 49-1010, Idaho Code, is adopted under the authority of Sections 40-312 and 49-1004, Idaho Code. (9-14-92)

001. TITLE AND SCOPE.

01. Title. This rule shall be cited as IDAPA 39.03.12, "Rules Governing Safety Requirements of Overlegal Permits," IDAPA 39, Title 03, Chapter 12. (4-5-00)

02. Scope. This rule states the requirements for pilot cars, oversize load signs, red warning flags, and lighting. (4-5-00)

002. -- 009. (RESERVED).

010. DEFINITIONS.

Refer to Rule 39.03.01 for definitions of the terms used in this rule. (10-2-89)

011. -- 099. (RESERVED).

100. LIGHTING REQUIREMENTS FOR OVERSIZE VEHICLES AND/OR LOADS TRAVELING AFTER DARK.

Those overdimensional vehicles and/or loads traveling during hours of darkness shall be required to display lights to mark the extremities of the vehicle and/or load, and shall be in addition to those clearance lights required on legal size vehicles when traveling at night. (4-5-00)

01. Standards for Lights on Oversize Vehicles and/or Loads. (4-5-00)

a. Lights are only required on those vehicles traveling after dark. (dark is defined as one-half (1/2) hour after sunset to one-half (1/2) hour before sunrise). (4-5-00)

b. The lights must be visible from a minimum of five hundred (500) feet. (4-5-00)

c. The lights shall be steady burning. (4-5-00)

d. The color of the lights shall be as follows: (4-5-00)

i. Lights visible from the front of the vehicle or loads and the extremities in the middle or near the front of the vehicle or load shall be amber. (4-5-00)

ii. Lights visible from the back of the vehicle or load and the extremities near the back of the vehicle or load shall be red. (4-5-00)

02. Standards for Lights on Rear Overhang. Lights are required when rear overhang exceeds the end of the trailer by four (4) feet or more. (4-5-00)

a. If the overhang is two (2) feet wide or less only one (1) light is required on the end of the overhang. (4-5-00)

b. If the overhang is over two (2) feet wide, two (2) lights are required on the end of the overhang to show the maximum width of the overhang. (4-5-00)

03. Standards for Warning Lights on Towing Vehicle. Amber flashing lights displayed on a towing vehicle operating at night, shall be mounted above the cab and meet the following: Rotating or flashing beacon visible from a minimum of five hundred (500) feet. (4-5-00)

101. -- 199. (RESERVED).

200. FLAGGING REQUIREMENTS FOR OVERSIZE VEHICLES AND/OR LOADS.

Warning flags for oversize vehicles and/or loads, excluding extra-length vehicle combinations, shall be marked by warning flags meeting the following: (4-5-00)

01. Warning Flags. Warning flags are required on all overwidth vehicles and/or loads and when the rear overhang exceeds the end of the trailer by four (4) feet or more. (4-5-00)

02. Size. Minimum size of flags is twelve (12) inches by twelve (12) inches. (4-5-00)

03. Color. Red or fluorescent orange. (4-5-00)

04. Placement of Flags. On overwidth vehicles and/or loads, flags shall be placed at the four (4) corners and/or extremities of the vehicle and/or load as follows: (4-5-00)

a. Front. Fastened to each front corner of the vehicle and/or load if it exceeds legal width. (4-5-00)

b. Rear. Fastened to each rear corner of the vehicle and/or load if it exceeds legal width. (4-5-00)

c. Side. Fastened to mark any extremity, when extremity is wider than the front or the rear of the vehicle and/or load. (4-5-00)

d. Overhang. If the overhang is two (2) feet wide or less only one (1) flag is required on the end of the overhang. If the overhang is over two (2) feet wide, two (2) flags are required on the end of the overhang to show the maximum width of the overhang. (4-5-00)

201.-- 299. (RESERVED).

300. SIGNING REQUIREMENTS OF OVERSIZE VEHICLES AND/OR LOADS.

Oversize load signs shall meet the following specifications: (4-5-00)

01. Dimensions. Eighteen (18) inches high by seven (7) feet wide, letter height ten (10) inches, letter type standard series C, stroke width one and five-eighths (1 5/8) inch, black letters on yellow background. (4-5-00)

02. Displaying Signs. Signs shall be displayed on the front of the towing vehicle and the rear of the oversize load. Shall be displayed on the front and back of self propelled oversize vehicles. (4-5-00)

03. When Signs Are Required. Oversize load signs shall be required on all vehicles and/or loads exceeding legal width. Signs shall not be displayed when the vehicle is empty and of legal dimensions. (4-5-00)

301. -- 399. (RESERVED).

400. PILOT/ESCORT VEHICLES.

Pilot/escort vehicle(s) shall be furnished by the permittee and shall be either passenger car(s), light truck(s) or vehicles authorized by the Vehicle Size & Weight Specialist. The light truck(s) used as pilot/escort vehicle(s) shall not be loaded in such a manner as to cause confusion to the public as to which vehicle is the one under escort. Vehicles towing trailers shall not qualify as pilot/escort vehicles. (4-5-00)

401. -- 499. (RESERVED).

500. PILOT/ESCORT VEHICLE SIGN REQUIREMENTS.

01. Oversize Load Signs. All pilot/escort vehicles while escorting and oversize load shall display a sign having the words OVERSIZE LOAD. Such signs shall not be displayed and shall be considered illegal except when the pilot/escort vehicle is actually piloting/escorting an oversize load. (4-5-00)

02. Dimensions. Ten (10) inches high by five (5) feet wide, type standard series B, eight (8) inch high letters, one (1) inch stroke width, and black letters on yellow background. (4-5-00)

501. -- 599. (RESERVED).

600. PILOT/ESCORT VEHICLE LIGHTING REQUIREMENTS.

01. Multiple Lights. Flashing or rotating amber lights displayed on the pilot/escort vehicle shall be mounted at each end of the required OVERSIZE LOAD sign above the roofline of the vehicle and be visible from the front and rear of the pilot/escort vehicle. These lights shall meet the minimum standards outlined under oversize vehicle and/or load lighting requirements. (4-5-00)

02. Single Light. As an alternate, a pilot/escort vehicle may display one (1) rotating or flashing amber beacon visible from a minimum of five hundred (500) feet, mounted above the roofline and visible from the front and rear of the pilot/escort vehicle. (4-5-00)

601. -- 699. (RESERVED).

700. PILOT/ESCORT VEHICLE EQUIPMENT.

01. Required Equipment to Be Carried in a Pilot/Escort Vehicle. A pilot/escort vehicle shall carry the following items of equipment when piloting/escorting an overlegal vehicle and/or load. (4-5-00)

- a.** Standard eighteen (18) inch STOP and SLOW paddle sign. (4-5-00)
- b.** Three (3) bi-directional emergency reflective triangles. (4-5-00)
- c.** A minimum of one (1) five (5) pound B, C, fire extinguisher. (4-5-00)
- d.** A reflectorized orange vest, shirt, or jacket, which must be worn by the operator when working out of the vehicle. (4-5-00)
- e.** Two (2) additional oversize load signs. (4-5-00)
- f.** Non-metallic Height Pole for determining vertical clearances (when required). (4-5-00)
- g.** Valid drivers license. (4-5-00)
- h.** Two-Way Radio. (4-5-00)

02. Two-Way Radio. On all movements requiring a pilot/escort vehicle, both the towing unit and the pilot/escort vehicle(s) shall be equipped with two-way radio equipment licensed under Federal Communications Commission regulations adequate to provide reliable voice communication between the drivers thereof at all times during the movement of the piloted/escorted vehicle and/or load. Transmitting and receiving capabilities of the radio equipment used shall be adequate to provide the required communication over a minimum distance of one-half (1/2) mile separation under conditions normally encountered along the proposed route. (4-5-00)

03. Radio Communications. Radio communication shall be open and monitored between the pilot/escort vehicle(s) and oversize vehicle and/or load at all times during movement. (4-5-00)

701. -- 799. (RESERVED).

800. PILOT/ESCORT VEHICLE PLACEMENT.

01. Front Pilot/Escort Vehicle. The movement of an oversize vehicle and/or load shall be preceded by a pilot/escort vehicle on those sections of highway where the vehicle and/or load cannot travel within its proper travelway lane. (4-5-00)

02. Rear Pilot/Escort Vehicle. As authorized by Section 49-940, Idaho Code, when the width of a load obstructs the driver's view to the rear or when traffic control is required, a rear escort shall be required to accompany the oversize load and to communicate with the driver of the permitted load concerning impeded overtaking traffic for the purpose of providing passing opportunity. (4-5-00)

03. Advance Pilot/Escort Vehicle. A third pilot/escort vehicle may be required when the load is of such extreme dimensions for the route of travel as to require holding opposing traffic at turnouts and intersections to provide for passage of the load. (4-5-00)

04. First Movement from the Forest. A pilot/escort vehicle is not required on the first movement from the forest of tree-length logs or poles if the overall length does not exceed one hundred ten (110) feet. Secondary movements must comply with the requirements stated on the Pilot/Escort Vehicle and Travel Time Requirements map. (4-5-00)

05. Spacing. Approximately one thousand (1,000) feet shall be maintained in rural areas between the piloting/escorting vehicle and any oversize load. This spacing may be reduced in urban areas when necessary to provide traffic control for turning movements. (4-5-00)

801. -- 899. (RESERVED).

900. CONVOY OF OVERLEGAL LOADS.

01. Convoying Oversize Loads. Oversize loads which individually would require a pilot/escort vehicle, except overwidth manufactured homes, office trailers, may be permitted to travel in convoy with pilot/escort vehicles in front of and behind the convoy, but such convoys shall not exceed four (4) oversize loads or vehicles between pilot/escort vehicles. Maximum width of units in a convoy shall be limited to fourteen (14) feet six (6) inches on the interstate system or on black-coded routes of the Pilot/Escort Vehicle and Travel Time Requirements Map and to twelve (12) feet six (6) inches on red-coded routes of the Pilot/Escort Vehicle and Travel Time Requirements Map. Oversize loads which do not individually require an pilot/escort vehicle may travel in convoy without pilot/escort vehicles. Maximum length of units in a convoy shall be limited to one hundred (100) feet on red-coded and black-coded routes of the pilot/escort vehicle and travel time requirements map and one hundred twenty (120) feet on the interstate system. (4-5-00)

02. Convoying Manufactured Homes, Office Trailers. No convoy of overwidth manufactured homes and office trailers shall include more than two (2) units and two (2) piloting/escorting vehicles. On those routes where pilot/escort vehicles are required in front and rear of an overwidth manufactured home and office trailers, two (2) units may travel in convoy between such piloting/escorting vehicles. On routes requiring only a front pilot/escort vehicle, the manufactured home and office trailers mover may have the option of convoying two (2) units between front and rear pilots/escorts. At no time shall more than one (1) manufactured home or office trailer be piloted/escorted by one (1) pilot/escort vehicle. Minimum spacing of approximately one thousand (1000) feet shall be maintained between all units in a convoy except when an pilot/escort is required to control traffic in turning movements. (4-5-00)

901. -- 949. (RESERVED).

950. PILOT/ESCORT VEHICLE AND TRAVEL TIME REQUIREMENTS MAP.

Color-coded maps on pilot/escort vehicle and travel time requirements for overwidth loads are available from the Headquarters Overlegal Permit Office, Ports of Entry and all Highway District offices for the information of enforcement officers and the trucking industry. The routes chosen as depicted on the Map are based on ability of the road to carry the over-all maximum width of load (not just base width) and character of the route of travel. (4-5-00)

951. -- 999. (RESERVED).

Subject Index

A

Advance Pilot/Escort Vehicle,
Placement 5

C

Convoy Of Overlegal Loads 5
Convoing Manufactured Homes,
Office Trailers 5
Convoing Oversize Loads 5

D

Definitions, IDAPA 39.03.12, Rules
Governing Safety Requirements Of
Overlegal Permits 2
Dimensions, Pilot/Escort Vehicle Sign
Requirements 4
Dimensions, Signing Requirements of
Oversize Vehicles & Loads 3
Displaying Signs, Signing
Requirements of Oversize Vehicles &
Loads 3

F

First Movement From The Forest,
Placement 5
Flagging Requirements For Oversize
Vehicles & Loads 3
Front Pilot/Escort Vehicle,
Placement 5

L

Lighting Requirements For Oversize
Vehicles & Loads Traveling After
Dark 2

M

Multiple Lights, Pilot/Escort Vehicle
Lighting Requirements 4

O

Oversize Load Signs, Pilot/Escort
Vehicle Sign Requirements 4

P

Pilot/Escort Vehicle & Travel Time
Requirements Map 5
Pilot/Escort Vehicle Equipment 4
Pilot/Escort Vehicle Lighting
Requirements 4
Pilot/Escort Vehicle Placement 4
Pilot/Escort Vehicle Sign
Requirements 3
Pilot/Escort Vehicles 3
Placement of Flags, Requirements for
Oversize Vehicles & Loads 3

R

Rear Pilot/Escort Vehicle,
Placement 5

Required Equipment to be Carried in a
Pilot/Escort Vehicle 4

S

Signing Requirements Of Oversize
Vehicles & Loads 3
Single Light, Pilot/Escort Vehicle
Lighting Requirements 4
Spacing, Pilot/Escort Vehicle
Placement 5
Standards for Lights on Oversize
Vehicles & Load 2
Standards for Lights on Rear
Overhang 2
Standards for Warning Lights on
Towing Vehicle 3

T

Two-Way Radio, Pilot/Escort Vehicle
Equipment 4

W

Warning Flags, Requirements for
Oversize Vehicles & Loads 3
When Signs Are Required, Signing
Requirements of Oversize Vehicles &
Loads 3