

Table of Contents

17.08.11 - Idaho Minimum Safety Standards and Practices for Logging -- Skidding and Yarding

000. Legal Authority.	2
001. Title And Scope.	2
002. Written Interpretations.	2
003. Administrative Appeals.	2
004. -- 008. (Reserved).	2
009. Definitions.	2
010. Skidding And Yarding.	2
011. -- 999. (Reserved).	3

**IDAPA 17
TITLE 08
CHAPTER 11**

**17.08.11 - IDAHO MINIMUM SAFETY STANDARDS AND PRACTICES FOR LOGGING --
SKIDDING AND YARDING**

000. LEGAL AUTHORITY.

Pursuant to the provisions of Section 72-508, Idaho Code, the Industrial Commission has the authority to promulgate and adopt reasonable rules for effecting the purposes of the Workers' Compensation Act. (7-1-97)

001. TITLE AND SCOPE.

These rules shall be cited as IDAPA 17.08.11, "Idaho Minimum Safety Standards and Practices for Logging -- Skidding and Yarding," and shall be applicable to the logging industry in the state of Idaho. (7-1-97)

002. WRITTEN INTERPRETATIONS.

There are no written statements which pertain to the interpretation of these rules. (7-1-97)

003. ADMINISTRATIVE APPEALS.

There are no provisions for administrative appeal of these rules. The procedure for appeals in safety matters is prescribed by Sections 72-714 and 72-718 through 72-722, Idaho Code. (7-1-97)

004. -- 008. (RESERVED).

009. DEFINITIONS.

For definitions refer to IDAPA 17.08.01, "Idaho Minimum Safety Standards and Practices for Logging -- General Provisions," Section 007. (7-1-97)

010. SKIDDING AND YARDING.

01. General Requirements. (7-1-97)

a. All personnel shall wear approved head protection and proper clothing at all times in skidding and yarding. (7-1-97)

b. Getting on or off moving equipment is strictly prohibited. (7-1-97)

c. Equipment operators shall move rigging only on signal of authorized person. (7-1-97)

d. Workers shall at all times watch for and protect themselves and their fellow workers from side-winders, rolling logs, up ending logs, snags, and other hazards caused by the movement of equipment, logs and/or lines. (7-1-97)

e. Chokers should be placed near, but not closer than two (2) feet, from the ends of logs if possible. (7-1-97)

f. Choker holes shall be dug from the uphill side of a log if there is any danger of its rolling. (7-1-97)

g. Knots shall not be used to connect separate lengths of chain or cable. (7-1-97)

h. Chaser (hooker) shall not unhook logs (trees) until rigging has stopped and equipment operator is aware of his location. (7-1-97)

i. Riding on drag or logs or any part of equipment used in skidding and yarding except in the area of the driver's seat is prohibited. (7-1-97)

j. A tool handle, stick, iron bar, or similar object shall be used in guiding lines onto drums. Guiding lines with hands is prohibited. (7-1-97)

- k.** Make sure all personnel are in the clear before skidding turn, drag, log, or tree into landing. (7-1-97)
 - l.** All personnel shall keep out of the bight of line and clear of running lines. (7-1-97)
 - m.** Logs shall not be swung over personnel. (7-1-97)
 - n.** Knot bumping should be done before log is loaded. (7-1-97)
- 011. -- 999. (RESERVED).**

Subject Index

D

Definitions, IDAPA 17.08.11, Idaho
Minimum Safety Standards &
Practices For Logging -- Skidding &
Yarding 2

G

General Requirements 2

S

Skidding & Yarding 2