# Table of Contents

39.03.22 - Rules Governin	g Overlegal Permits for	Extra-Length, Excess Weight,
and Up to 129,	,000 Pound Vehicle Com	ıbinations ´´

000. Legal Authority	2
001. Title And Scope	
002. Written Interpretations	
003. Administrative Appeals	2
004. Incorporation By Reference	2
005. Office Office Hours Mailing And Street Address Phone Numbers	2
006. Public Records Act Compliance	2
007 009. (Reserved)	2
010. Definitions	2
011 099. (Reserved)	2
100. Designated Routes For Extra Length Vehicle Combinations Carrying Up To O Hundred Five Thousand Five Hundred Pounds Shall Be Designated In Four	ne
Categories	2
101 199. (Reserved)	3
200. Designated Routes For Vehicle Combinations Up To One Hundred Twenty-Ni Thousand Pounds.	3
201 299. (Reserved)	3
300. Operating Requirements For Extra-Length, Excess Weight, And Up To 129,0 Pound Vehicle Combinations.	_
301 399. (Reserved)	4
400. Overlegal Permits For Operations Of Extra-Length, Excess Weight, And Up 1 129,000 Pound Vehicle Combinations.	
401 999. (Reserved)	5

#### IDAPA 39 TITLE 03 CHAPTER 22

### 39.03.22 - RULES GOVERNING OVERLEGAL PERMITS FOR EXTRA-LENGTH, EXCESS WEIGHT, AND UP TO 129,000 POUND VEHICLE COMBINATIONS

#### 000. LEGAL AUTHORITY.

This rule, governing the movement of vehicles which are in excess of the sizes allowed by 49-1004 and 49-1010, is adopted under the authority of Section 40-312, Idaho Code. (4-7-11)

#### 001. TITLE AND SCOPE.

**01. Title**. This rule shall be cited as IDAPA 39.03.22, "Rules Governing Overlegal Permits for Extra-Length, Excess Weight, and Up to 129,000 Pound Vehicle Combinations," IDAPA 39, Title 03, Chapter 22.

(7-1-13)T

**O2.** Scope. This rule states the requirements and routes for extra-length, excess weight and up to one hundred twenty-nine thousand (129,000) pound vehicle combinations. (7-1-13)T

#### 002. WRITTEN INTERPRETATIONS.

There are no written interpretations for this chapter.

(3-20-04)

#### 003. ADMINISTRATIVE APPEALS.

Administrative appeals under this chapter shall be governed by the rules of administrative procedure of the attorney general, IDAPA 04.11.01, "Idaho Rules of Administrative Procedure of the Attorney General." (3-20-04)

#### 004. INCORPORATION BY REFERENCE.

There are no documents incorporated by reference in this chapter.

(3-20-04)

#### 005. OFFICE -- OFFICE HOURS -- MAILING AND STREET ADDRESS -- PHONE NUMBERS.

- **01. Street And Mailing Address**. The Idaho Transportation Department maintains a central office in Boise at 3311 W. State Street with a mailing address of PO Box 7129, Boise, ID 83707-1129. (3-20-04)
- **Office Hours**. Daily office hours are 7:30 a.m. to 5 p.m. except Saturday, Sunday and state holidays. (4-7-11)
- **03. Telephone and Fax Numbers**. The central office may be contacted during office hours by phone at 208-334-8420, 1-800-662-7133 or by fax at 334-8419. (7-1-13)T

#### 006. PUBLIC RECORDS ACT COMPLIANCE.

All records associated with this chapter are subject to and in compliance with the Idaho Public Records Act, as set forth in Sections 9-337 through 9-350, Idaho Code. (3-20-04)

#### 007. -- 009. (RESERVED)

#### 010. DEFINITIONS.

Refer to IDAPA 39.03.01, "Rules Governing Definitions," for definitions of the terms used in this rule. (10-2-89)

#### 011. -- 099. (RESERVED)

# 100. DESIGNATED ROUTES FOR EXTRA LENGTH VEHICLE COMBINATIONS CARRYING UP TO ONE HUNDRED FIVE THOUSAND FIVE HUNDRED POUNDS SHALL BE DESIGNATED IN FOUR CATEGORIES.

The "Extra Length Map" listing the designated routes for vehicles operating up to one hundred five thousand five hundred (105,500) pounds is available at the Idaho Transportation Department offices. This map is not the same as the "Designated Routes Up to 129,000 Pound Map" listed in Section 200. (7-1-13)T

Section 000 Page 2

- **O1. Blue-Coded Routes.** Routes for combinations not exceeding ninety-five (95) feet in overall length including load overhang (blue-coded routes). A vehicle combination operating on routes designated for up to ninety-five (95) feet shall be designed and assembled in a manner whereby its maximum off-tracking will not exceed five point five zero (5.50) feet on a one hundred sixty-five (165) foot radius when computed. (7-1-13)T
- **Red-Coded Routes**. Routes for combinations of vehicles not exceeding one hundred fifteen (115) feet in overall length including load overhang (red-coded routes). A vehicle combination operating on routes designated for up to one hundred fifteen (115) feet shall be designed and assembled in a manner whereby its maximum off-tracking will not exceed six point five zero (6.50) feet on a one hundred sixty-five (165) foot radius when computed. (7-1-13)T
- **O3. Black-Coded Routes**. Interstate system routes and specified interchanges providing access to approved breakdown areas located in close proximity to the Interstate system (black-coded routes). A vehicle combination operating on routes in this category shall be designed and assembled in such a manner that its off-tracking may exceed six point five zero (6.50) feet but shall not exceed eight point seventy-five (8.75) feet when computed. Specified interchanges providing access to approved breakdown areas are required to be used by combinations that exceed six point five zero (6.50) feet off-tracking. The specified interchanges will be authorized for either combinations in excess of six point five zero (6.50) feet off-tracking, but not in excess of seven (7) feet off-tracking, or for combinations in excess of seven (7) feet off-tracking but not in excess of eight point seventy-five (8.75) feet off-tracking.
- **04. Green-Coded Routes.** Selected state highway routes (green coded routes) for operation of a vehicle combination whereby its maximum off-tracking will not exceed three (3) feet on a one hundred sixty-five (165) foot radius when computed, and its overall length including load overhang does not exceed eighty-five (85) feet. Route approval shall be subject to analysis of pavement condition, bridge capacity, safety considerations, pavement width, curvature, traffic volumes and traffic operations. (7-1-13)T

#### 101. -- 199. (RESERVED)

### 200. DESIGNATED ROUTES FOR VEHICLE COMBINATIONS UP TO ONE HUNDRED TWENTY-NINE THOUSAND POUNDS.

In addition to the requirements listed in Sections 300 and 400, vehicle combinations operating up to one hundred twenty-nine thousand (129,000) pounds, must meet the following requirements: (7-1-13)T

- **O1. Brakes**. All axles shall be equipped with brakes that meet the Federal Motor Carrier Safety Regulations. (7-1-13)T
- **02. Permits**. Permits will be vehicle specific and will be in addition to any extra length and excess weight permit for operation of vehicle combinations at weights up to one hundred five thousand five hundred (105,500) pounds. (7-1-13)T
- **O3. Designated Routes.** All designated state approved routes for vehicle combinations to operate at weights above one hundred five thousand five hundred (105,500) pounds will be identified on the "Designated Routes Up to 129,000 Pound Map" which is available at the Idaho Transportation Department. (7-1-13)T
- a. Routes for combinations of vehicles not exceeding one hundred fifteen (115) feet in overall length including load overhang (magenta-coded routes). A vehicle combination operating on routes designated for up to one hundred fifteen (115) feet shall be designed and assembled in a manner whereby its maximum off-tracking will not exceed six point five zero (6.50) feet on a one hundred sixty-five (165) foot radius when computed. (7-1-13)T

#### 201. -- 299. (RESERVED)

### 300. OPERATING REQUIREMENTS FOR EXTRA-LENGTH, EXCESS WEIGHT, AND UP TO 129,000 POUND VEHICLE COMBINATIONS.

All vehicle combinations shall be subject to the following conditions, limitations, and requirements: (7-1-13)T

Section 200 Page 3

- **01.** Cargo Carrying Units. Vehicle combinations operating with an overall length in excess of the limits imposed in Section 49-1010, Idaho Code, shall consist of not more than four (4) units, shall not exceed one hundred fifteen (115) feet overall and no such vehicle combination shall include more than three (3) cargo units except that a full truck and full trailer may have an overall length in excess of seventy-five (75) feet but not in excess of eighty-five (85) feet including load overhang. (7-1-13)T
- **Power Unit.** The power unit of all vehicle combinations shall have adequate power and traction to maintain a minimum of twenty (20) miles per hour under normal operating conditions on any up-grade over which the combination is operated. (10-2-89)
- **O3.** Connecting Devices. Fifth wheel, drawbar, and other coupling devices shall be as specified by Federal Motor Carrier Safety Regulations, Part 393. (4-7-11)
- **Hazardous Travel Conditions Restrictions.** Extreme caution in the operation of permitted vehicle combinations shall be exercised when hazardous conditions exist. The movement of overlegal vehicles and/or loads by overlegal permit shall be prohibited and otherwise valid permits shall automatically become invalid en route when travel conditions become hazardous. Hazardous conditions include, but are not limited to, ice, snow or frost; or when visibility is restricted to less than five hundred (500) feet. (7-1-13)T
- **O5. Trailer Weight Sequence.** In any extra-length combination, the respective loading of any trailer shall not be substantially greater than the weight of any trailer located ahead of it in the vehicle combination. (Substantially greater shall be defined as more than four thousand (4,000) pounds heavier.) (10-2-89)
- **06. Operating Restrictions**. Operators of all vehicle combinations governed by this rule shall comply with the following operating restrictions: (8-25-94)
- **a.** A minimum distance of five hundred (500) feet shall be maintained between combinations of vehicles except when overtaking and passing. (10-2-89)
- **b.** Except when passing another vehicle traveling in the same direction, the combination shall be driven so as to remain at all times on the right hand side of the centerline of a two (2) lane, two (2) way highway, or on the right hand side of a lane stripe or marker of a highway of four (4) or more lanes. (1-1-90)
  - c. Be in compliance with all Federal Motor Carrier Safety Regulations. (3-22-00)
- **07. Insurance Requirements.** Every vehicle combination operated under this rule shall be covered by insurance of not less than five hundred thousand dollars (\$500,000) combined single limit. The permittee or driver of the permitted vehicle combination shall carry in the vehicle evidence of insurance written by an authorized insurer to certify that insurance in this minimum amount is currently in force. (7-1-13)T
- **O8.** Tire Limitations. Single axles on vehicle combinations shall be equipped with four (4) tires except on the steering axle, or variable load suspension axles (VLS-lift axles), unless equipped with fifteen (15) inch wide or wider single tires. Multiple axle configurations may be equipped with single tires on each of the axles as long as the pounds-per-inch width of tire does not exceed six hundred (600) pounds, the manufacturers rating or legal weights whichever is less.

  (7-1-13)T
  - **09. Brakes**. Brakes shall meet the Federal Motor Carrier Safety Regulations. (7-1-13)T
- **301. -- 399.** (RESERVED)
- 400. OVERLEGAL PERMITS FOR OPERATIONS OF EXTRA-LENGTH, EXCESS WEIGHT, AND UP TO 129,000 POUND VEHICLE COMBINATIONS.
- **01. Permit Attachments.** All vehicles in operation shall be allowed to travel under the authority of overlegal permits issued to the power unit. A copy of this rule shall accompany and shall be a part of all annual extralength, excess weight, and up to 129,000 pound permits. An allowable gross loads table shall accompany and be referred to on the face of the permit. Operations shall be valid only on routes of the state highway system designated

Section 400 Page 4

for such purposes as set forth on the "Extra Length Map" of designated routes, or the "Designated Routes Up to 129,000 Pound Map," which shall accompany the permit, and is available at the overlegal permit office and ports of entry.

(7-1-13)T

- **O2. Permit Requirements and Special Requirements**. Permits issued for operations of extra-length, excess weight, and up to 129,000 pound vehicle combinations shall be subject to the general requirements of Section 300, and to the following special conditions. (7-1-13)T
- a. The operator of any extra-length, excess weight, and up to 129,000 pound vehicle combination shall complete the Off-Track Computation Form to provide internal dimensions of the combination and computation of off-track as evidence of compliance with maximum off-track requirements specified for the designated route being traveled. The completed Off-Track Computation Form, when required, shall be available for inspection by enforcement officers with the permit for the vehicle combination. When the Off-Track Computation Form is required, permit shall be invalid until the form is completed and available for inspection. (7-1-13)T
- **b.** Permits shall become automatically invalid subject to conditions cited in IDAPA 39.03.23, "Rules Governing Revocation of Special Permits." (7-1-13)T
- **03.** Exceeding Allowed Length and/or Off-Track Limitations. Extra-length, excess weight, and up to 129,000 pound vehicle combinations apprehended for exceeding allowed length and/or off-track limitations as set forth in this rule shall be subject to the following course of action: (7-1-13)T
- **a.** The vehicle combination will be escorted by the apprehending officer to the first safe parking location; and (8-25-94)
- **b.** The driver of the vehicle combination will be issued a single trip, one (1) day permit via a specified route to the nearest permitted route. The condition of this permit shall require an advance pilot/escort vehicle to escort the extra-length vehicle combination, and the pilot/escort vehicle shall meet the pilot/escort vehicle requirements as set forth in IDAPA 39.03.12, "Rules Governing Safety Requirements of Overlegal Permits." (7-1-13)T

**401.** -- **999.** (**RESERVED**)

Section 400 Page 5

## Subject Index

#### D

Definitions, IDAPA 39.03.22, Rules Governing Overlegal Permits For Extra-Length Vehicle Combinations 2 Designated Routes For Extra Length Vehicle Combinations Carrying Up To One Hundred Five Thousand Five Hundred Pounds Shall Be Designated In Four Categories 2 Black-Coded Routes 3 Blue-Coded Routes 3 Green-Coded Routes 3 Red-Coded Routes 3 Designated Routes For Vehicle Combinations Up To One Hundred Twenty-Nine Thousand Pounds 3 Brakes 3 Designated Routes 3 Permits 3

#### 0

Operating Requirements For Extra-Length, Excess Weight, & Up To 129,000 Pound Vehicle Combinations 3 Brakes 4 Cargo Carrying Units 4 Connecting Devices 4 Hazardous Travel Conditions Restrictions 4 Insurance Requirements 4 Operating Restrictions 4 Power Unit 4 Tire Limitations 4 Trailer Weight Sequence 4 Overlegal Permits For Operations Of Extra-Length, Excess Weight, & Up To 129,000 Pound Vehicle Combinations 4 Exceeding Allowed Length and/or Off-Track Limitations 5 Permit Attachments 4 Permit Requirements & Special Requirements 5

