Table of Contents

07.08.05 – Idaho Minimum Safety Standards and Practices for Logging – Signals and Signal Systems

000. Legal Authority.	2
001. Title And Scope.	
002. Written Interpretations.	2
003. Administrative Appeals.	2
004. Incorporation By Reference.	
005. Office - Office Hours - Mailing Address And Street Address.	2
006. Public Records Act Compliance.	2
007 008. (Reserved)	2
009. Definitions.	
010. General Requirements.	2
011. Signaling.	3
012. Electric Signal Systems.	
013. Radio Signaling Systems.	
014 999. (Reserved)	

IDAPA 07 TITLE 08 CHAPTER 05

07.08.05 – IDAHO MINIMUM SAFETY STANDARDS AND PRACTICES FOR LOGGING – SIGNALS AND SIGNAL SYSTEMS

000. LEGAL AUTHORITY.

Pursuant to the provisions of Section 67-2601A, Idaho Code, the Division of Building Safety has the authority to promulgate and adopt rules for affecting the purposes therein. (3-29-17)

001. TITLE AND SCOPE.

These rules shall be cited as IDAPA 07.08.05, "Idaho Minimum Safety Standards and Practices for Logging – Signals and Signal Systems," and shall be applicable to the logging industry in the state of Idaho. (7-1-97)

002. WRITTEN INTERPRETATIONS.

There are no written statemer	its which pertain to	the interpretation of these rules.	(7-1-97)

003. ADMINISTRATIVE APPEALS.

The procedure for appeals in logging safety matters is prescribed by IDAPA 07.08.16, "Idaho Minimum Safety Standards and Practices for Logging – Recommended Safety Program," and Title 67, Chapter 52, Idaho Code.

(3-29-17)

004. INCORPORATION BY REFERENCE.

There are no documents that have been incorporated by reference into these rules. (3-29-17)

005. OFFICE – OFFICE HOURS – MAILING ADDRESS AND STREET ADDRESS.

The principal place of business of the Division of Building Safety, Logging Safety Program, is at the Division office located at 1090 E. Watertower Street, Suite 150, Meridian, Idaho 83642. The Logging Safety Program may also be contacted at 1250 Ironwood Drive, Suite 220, Coeur d'Alene, Idaho 83814, and at 2055 Garrett Way, Suite 4, Pocatello, Idaho 83201. All locations are open from 8:00 a.m. to 5:00 p.m., except Saturday, Sunday and legal holidays. The telephone number of the office is (208) 334-3950. The facsimile number of the office is 1-877-810-2840. The Department website is http://dbs.idaho.gov. (3-29-17)

006. PUBLIC RECORDS ACT COMPLIANCE.

The rules contained herein have been promulgated according to the provisions of Title 67, Chapter 52, Idaho Code, and are public records. (3-29-17)

007. -- 008. (RESERVED)

009. **DEFINITIONS**.

For definitions refer to IDAPA 07.08.01, "Idaho Minimum Safety Standards and Practices for Logging -- General Provisions," Section 007, and IDAPA 07.08.15, "Idaho Minimum Safety Standards and Practices for Logging -- Commonly Used Logging Terms. (3-29-17)

010. GENERAL REQUIREMENTS.

01.	Rigging.	(7-1-97)
a.	Rigging shall be moved by established signals and procedures only.	(7-1-97)
b.	Signals shall be thoroughly understood by the crew.	(7-1-97)
02.	Daily Test Required. Each electric or radio signal system shall be tested daily before	operations (7-1-97)
03.	Personnel in Clear Before Moving Logs or Turns.	(7-1-97)

begin.

IDAHO ADMINISTRATIVE CODEIDAPA 07.08.05 – Minimum Safety Standards & PracticesDivision of Building Safetyfor Logging – Signals & Signal Systems

a signa	a. l has been	Operators of yarding equipment shall not move logs or turns until all personnel are in the a given.	e clear and (7-1-97)
	b.	Operators of yarding equipment shall be alert to signals at all times.	(7-1-97)
011.	SIGNA	LING.	
	01.	One Worker to Give Signals.	(7-1-97)
	a.	The Worker sending drag shall be the only one to give signals.	(3-29-17)
conditi	b. ons are ap	Any person is authorized to give a stop signal when a worker is in danger or other exparent.	emergency (3-29-17)
	02.	Signal Must Be Clear and Distinct.	(7-1-97)
	a.	Machine operators shall not move any line unless the signal received is clear and distinct	. (7-1-97)
	b.	If in doubt the operator shall repeat the signal as understood and wait for confirmation.	(7-1-97)
	03.	Hand Signal Use Restricted.	(7-1-97)
	a.	Hand signals are permitted only when in plain sight of the operator.	(7-1-97)
	b.	Hand signals may be used at any time as an emergency stop signal.	(7-1-97)
move l	04. ogs or tur	Persons in Clear Before Signal Given . All persons shall be in the clear before a signal ns.	is given to (7-1-97)
	05.	Throwing Material Prohibited. Throwing of any type of material as a signal is prohibit	ed. (7-1-97)
operati	06. ons is pro	Use of Jerk Wire Prohibited. The use of a jerk wire whistle system for any type of hibited.	of yarding (3-29-17)
clearly	07. audible to	Audible Signaling to Be Installed and Used. A whistle, horn or other audible signality of all persons in the affected area, shall be installed and used on all machines operating as y	
transm	08. ission is u	Audible Signaling Device at the Machine to Be Activated. When radio or other mean used, an audible signal must be activated at the machine.	s of signal (7-1-97)
012.	ELECT	TRIC SIGNAL SYSTEMS.	
01. Weatherproof Wire and Attachments to Be Used. Where an electrical signal system is used, all wire and attachments shall be of the weather proof type. (7-1-97)			
proper! mainta	02. ly installe ined in go	Electric Signal Systems to Be Properly Installed and Adjusted . Electric signal system and adjusted as necessary. They shall be protected against accidental signaling, and and operating condition at all times.	
weathe	03. erproof.	All Connections to Be Weatherproof. All connections in insulated signal wire	shall be (7-1-97)
013.	RADIC) SIGNALING SYSTEMS.	

013. RADIO SIGNALING SYSTEMS.

01. Use of Conventional Space Transmission of Radio Signals. When conventional space

IDAHO ADMINISTRATIVE CODE IDAPA 07.08.05 – Minimum Safety Standards & Practices Division of Building Safety for Logging – Signals & Signal Systems

transmission of radio signals is used under and in accordance with an authorization granted by the Federal Communications Commissions to initiate any whistle, horn, bell or other audible signaling device, or such transmission of radio signals is used to activate or control any equipment, the following specific rules contained in this section will apply.

NOTE: This rule shall apply only to devices operating on radio frequencies authorized pursuant to the rules and regulations of the Federal Communications Commission. (3-29-17)

02. Description on Outside of Case.

a. Each radio transmitter and receiver shall have its tone frequency(s) in hertz (CPS), the manufacturer's serial number, and the assigned radio frequency clearly and permanently indicated on the outside of the case. (7-1-97)

b. When the duration of a tone frequency performs a function, the pulse-tone duration shall also be permanently indicated on the outside of the case. (3-29-17)

c. On the FCC restricted frequencies one hundred fifty-four point fifty-seven (154.57) MHZ and one hundred fifty-four point sixty (154.60) MHZ, a maximum of two (2) watts of power will be allowed. (7-1-97)

03. Activating Pulse-Tone Limitations. The activating pulse-tone of any multi-tone transmitter shall be of not more than forty (40) milliseconds duration. (7-1-97)

04. Adjustment, Repair or Alteration. All adjustments, repairs or alterations of radio-signaling devices shall be done only by or under the immediate supervision and responsibility of a person holding a first or second class commercial radio operator's license, either radio-telephone or radio-telegraph, issued by the Federal Communications Commission. (7-1-97)

05. Testing of Tone-Signal Controlled Devices. (7-1-97)

a. Tone-signal controlled devices shall be tested each day before work begins. If any part of the equipment fails to function properly, the system shall not be used until the source of trouble is detected and corrected. (7-1-97)

b. Audible signals used for test purposes shall not include signals used for movement of lines or material.

NOTE: Equipment or machines controlled by radio-signaling devices shall be designed and built to "fail safe" or stop, in case of failure of the radio-signaling device. (3-29-17)

06. Interference, Overlap, Fade-Out or Blackout. When interference, overlap, fade-out or blackout of radio signals is encountered, the use of the tone-signal controlled device shall be immediately discontinued. The use of such tone-signal controlled device shall not be resumed until the source of trouble has been detected and corrected. (7-1-97)

07. Number of Transmitters Required.

a. Two (2) radio transmitters shall be in the vicinity of the rigging crew at all times when transmitters are being used by persons who are around the live rigging. (7-1-97)

b. Only one (1) radio transmitter shall be required, if in possession of a signalman who has no other duties and remains in an area where he is not subjected to hazards created by moving logs or rigging. (3-29-17)

08.	Voice Communication.	(7-1-97)
a.	Voice Communication shall be used for explanation purposes only.	(7-1-97)

(7-1-97)

(7 - 1 - 97)

IDAHO ADMINISTRATIVE CODEIDAPA 07.08.05 – Minimum Safety Standards & PracticesDivision of Building Safetyfor Logging – Signals & Signal Systems

b. Actual activation of equipment shall be done by audible horn, bell or whistle and not by voice. (7-1-97)
c. The signal must be audible throughout the entire yarding and machine area. (7-1-97)

014. -- 999. (RESERVED)

Subject Index

D

Definitions, IDAPA 07.08.05, Idaho Minimum Safety Standards & Practices For Logging -- Signal & Signal Systems 2

E

Electric Signal Systems 3 All Connections to Be Weatherproof 3 Electric Signal Systems to be Properly Installed & Adjusted 3 Weatherproof Wire & Attachments to be Used 3

G

General Requirements 2 Daily Test Required 2 Personnel in Clear Before Moving Logs or Turns 2 Rigging 2

R

Radio Signaling Systems 3 Activating Pulse-Tone Limitations 4 Adjustment, Repair or Alteration 4 Description on Outside of Case 4 Interference, Overlap, Fade-Out or Blackout 4 Number of Transmitters Required 4 Testing of Tone-Signal Controlled Devices 4 Use of Conventional Space Transmission of Radio Signals 3 Voice Communication 4

S

Signaling 3 Audible Signaling Device at the Machine to be Activated 3 Audible Signaling to be Installed & Used 3 Hand Signal Use Restricted 3 One Worker to Give Signals 3 Persons in Clear Before Signal Given 3 Signal Must Be Clear & Distinct 3 Throwing Material Prohibited 3 Use of Jerk Wire Prohibited 3