

IDAPA 24 – DIVISION OF OCCUPATIONAL AND PROFESSIONAL LICENSES

IDAHO BUILDING CODE BOARD

24.39.30 – Rules of Building Safety (Building Code Rules)

Who does this rule apply to?

This rule applies to those who perform building construction in Idaho, and those who request plans examination and inspection services from the Division, including public entities and modular building manufacturers.

What is the purpose of this rule?

The rule adopts the specific editions of the building codes prescribed by Idaho Code, and adopted by the Idaho Building Code Board, along with amendments to such building codes as determined by the Board. The rule also provides the fees for building plans examination services, permits and inspections provided by the Division, as well as prescribes the authority, processes and other requirements related to how the Division performs inspections on all public buildings and school facilities, as well as for modular structures and manufactured homes.

What is the legal authority for the agency to promulgate this rule?

This rule implements the following statute(s) passed by the Idaho Legislature:

Health and Safety -

- [Title 39, Chapter 41, Idaho Code](#) – Idaho Building Code Act
- [Title 39, Chapter 43, Idaho Code](#) – Modular Buildings
- [39-4107, Idaho Code](#) – Powers and Duties
- [39-4109, Idaho Code](#) – Application of Codes

Who do I contact for more information on this rule?

Idaho Division of Building Safety
1090 E. Watertower Street, Suite 150
Meridian, ID 83642
Phone: (208) 334-3950
Fax: (877) 810-2840
Email: customer.service@dbs.idaho.gov
Website: <https://dbs.idaho.gov/>

Table of Contents

24.39.30 – Rules of Building Safety (Building Code Rules)

000. Legal Authority.	3
001. Title And Scope.	3
002. -- 003. (Reserved)	3
004. Adoption And Incorporation By Reference.	3
005. -- 025. (Reserved)	11
026. Definitions.	11
027. Permits.	13
028. Plan Review.	13
029. Fees.	14
030. Right Of Entry.	15
031. Work Proceeding Without Permit Or Approval.	15
032. Stop Work Orders.	16
033. Prohibited Sale Or Occupancy Notice.	16
034. Removal Of Orders And Notices; Sale, Rent, Lease Or Occupancy Of A Unit Bearing Such Order Or Notice.	16
035. Modular Buildings.	16
036. Manufactured Homes.	18
037. (Reserved)	19
038. Integrated Design And Fundamental Commissioning Of Public School Facilities.	19
039. -- 999. (Reserved)	20

24.39.30 – RULES OF BUILDING SAFETY (BUILDING CODE RULES)

000. LEGAL AUTHORITY.

The Idaho Building Code Board of the Division of Building Safety is authorized under Section 39-4107, Idaho Code, to promulgate rules concerning the enforcement and administration of the Idaho Building Code Act. (3-20-20)T

001. TITLE AND SCOPE.

01. Title. These rules are titled IDAPA 24.39.30, “Rules of Building Safety (Building Code Rules).” (3-20-20)T

02. Scope. These rules prescribe the criteria for enforcement and administration of the Idaho Building Code Act by the Idaho Building Code Board and the Division of Building Safety. (3-20-20)T

002. -- 003. (RESERVED)

004. ADOPTION AND INCORPORATION BY REFERENCE.

Under the provisions of Section 39-4109, Idaho Code, the codes enumerated in this section are hereby adopted and incorporated by reference into IDAPA 24.39.30, “Rules of Building Safety (Building Code Rules),” Division of Building Safety. Pursuant to Section 39-4109, Idaho Code, the effective date of any edition of the codes adopted in this Section, or any amendments identified thereto, shall be January 1 of the succeeding year following legislative approval of the rulemaking establishing the edition or amendment. Copies of these documents may be reviewed at the office of the Division of Building Safety. The referenced codes may be obtained from International Code Council, 5360 Workman Mill Road, Whittier, California 90601-2298 or the International Code Council at <http://www.iccsafe.org>. (3-20-20)T

01. International Building Code. 2018 Edition with the following amendments: (3-20-20)T

a. Delete Section 305.2.3 and replace with the following: 305.2.3 Twelve (12) or fewer children in a dwelling unit. A facility such as the above within a dwelling unit and having twelve (12) or fewer children receiving such day care shall be classified as a Group R-3 occupancy or shall comply with the International Residential Code. (3-20-20)T

b. Delete Section 308.2.4 and replace with the following: 308.2.4 Five (5) or fewer persons receiving custodial care. A facility with five (5) or fewer persons receiving custodial care shall be classified as a Group R-3 occupancy or shall comply with the International Residential Code. (3-20-20)T

c. Delete Section 308.3.2 and replace with the following: 308.3.2 Five (5) or fewer persons receiving medical care. A facility with five (5) or fewer persons receiving medical care shall be classified as a Group R-3 occupancy. (3-20-20)T

d. Delete Section 308.5.4 and replace with the following: 308.5.4 Persons receiving care in a dwelling unit. A facility such as the above within a dwelling unit and having twelve (12) or fewer children receiving day care or having five (5) or fewer persons receiving custodial care shall be classified as a Group R-3 occupancy or shall comply with the International Residential Code. (3-20-20)T

e. Delete Section 310.4 and replace with the following: 310.4 Residential Group R-3. Residential Group R-3 occupancies where the occupants are primarily permanent in nature and not classified as Group R-1, R-2, R-4, E or I, including: 1. Buildings that do not contain more than two (2) dwelling units. 2. Care facilities that provide accommodations for five (5) or fewer persons receiving personal care, custodial care or medical care. 3. Congregate living facilities (nontransient) with sixteen (16) or fewer occupants, including boarding houses (nontransient), convents, dormitories, fraternities and sororities, and monasteries. 4. Congregate living facilities (transient) with ten (10) or fewer occupants, including boarding houses (transient). 5. Dwelling units providing day care for twelve (12) or fewer children. 6. Lodging houses (transient) with five (5) or fewer guest rooms and ten (10) or fewer occupants. (3-20-20)T

f. Delete Section 310.4.1 and replace with the following: 310.4.1 Care facilities within a dwelling. Care facilities for twelve (12) or fewer children receiving day care or for five (5) or fewer persons receiving personal care or custodial care that are within a one- or two-family dwelling are permitted to comply with the International Residential Code. (3-20-20)T

g. Delete footnote ^e under Table 2902.1 Minimum Number of Required Plumbing Fixtures and replace with the following: ^e For business occupancies, excluding restaurants, and mercantile occupancies with an

occupant load of thirty (30) or fewer, service sinks shall not be required. (3-20-20)T

h. Delete footnote ^f from Table 2902.1 Minimum Number of Required Plumbing Fixtures, add footnote ^f in the header row of the column in Table 2902.1 labeled “Drinking Fountains,” and delete footnote ^f under Table 2902.1 and replace with the following: ^f Drinking fountains are not required for an occupant load of thirty (30) or fewer. (3-20-20)T

i. Delete Section 3113.1 and replace with the following: 3113.1 General. The provisions of this Section shall apply to relocatable buildings. Relocatable buildings manufactured after the effective date of this code shall comply with the applicable provisions of this code; title 39, chapter 43, Idaho Code; and IDAPA 24.39.31. Exception: This Section shall not apply to manufactured housing used as dwellings. (3-20-20)T

02. International Residential Code. 2018 Edition with the following amendments: (3-20-20)T

a. Delete the exception under Section R101.2 Scope, and replace with the following: Exception: The following shall also be permitted to be constructed in accordance with this code: 1. Owner-occupied lodging houses with five (5) or fewer guestrooms and ten (10) or fewer total occupants. 2. A care facility with five (5) or fewer persons receiving custodial care within a dwelling unit or single-family dwelling. 3. A care facility for five (5) or fewer persons receiving personal care that are within a dwelling unit or single-family dwelling. 4. A care facility with twelve (12) or fewer children receiving day care within a dwelling unit or single-family dwelling. (3-20-20)T

b. Delete Section R104.10.1 Flood hazard areas. (3-20-20)T

c. Delete item number 7 under the “Building” subheading of Section R105.2 Work exempt from permit, and replace with the following: 7. Prefabricated swimming pools that are not greater than four (4) feet (one thousand, two hundred nineteen (1219) mm) deep. (3-20-20)T

d. Add the following as item number 11 under the “Building” subheading of Section R105.2 Work exempt from permit: 11. Flag poles. (3-20-20)T

e. Delete Section R109.1.3 and replace with the following: R109.1.3 Floodplain inspections. For construction in areas prone to flooding as established by Table R301.2(1), upon placement of the lowest floor, including basement, the building official is authorized to require submission of documentation of the elevation of the lowest floor, including basement, required in Section R322. (3-20-20)T

f. Delete Section R301.2.1.2 Protection of Openings. (3-20-20)T

g. Delete Table R302.1(1) and replace with the following:

TABLE R302.1(1) - EXTERIOR WALLS

EXTERIOR WALL ELEMENT		MINIMUM FIRE-RESISTANCE RATING	MINIMUM FIRE SEPARATION DISTANCE
Walls	Fire-resistance rated	1 hour-tested in accordance with ASTM E 119, UL263, or Section 703.3 of the International Building Code with exposure from both sides	< 3 feet
	Not fire-resistance rated	0 hours	≥ 3 feet

EXTERIOR WALL ELEMENT		MINIMUM FIRE-RESISTANCE RATING	MINIMUM FIRE SEPARATION DISTANCE
Projections	Fire-resistance rated	1 hour on the underside, or heavy timber, or fire retardant-treated wood ^{a,b}	≥ 2 feet to < 3 feet
	Not fire-resistance rated	0 hours	≥ 3 feet
Openings in Walls	Not allowed	N/A	< 3 feet
	25% maximum of wall area	0 hours	≥ 3 feet to < 5 feet
	Unlimited	0 hours	5 feet
Penetrations	All	Comply with Section R302.4	< 3 feet
		None required	≥ 3 feet

For SI: 1 foot = 304.8 mm.

N/A = Not Applicable

^a The fire-resistance rating shall be permitted to be reduced to zero (0) hours on the underside of the eave overhang if fireblocking is provided from the wall top plate to the underside of the roof sheathing.

^b The fire-resistance rating shall be permitted to be reduced to zero (0) hours on the underside of the rake overhang where gable vent openings are not installed. (3-20-20)T

h. Delete Section R302.13 Fire protection of floors. (3-20-20)T

i. Delete Section R303.4 and replace with the following: R303.4 Mechanical Ventilation. Dwelling units shall be provided with whole-house mechanical ventilation in accordance with Section M1505.4. (3-20-20)T

j. Delete the exception under Section R313.1 Townhouse automatic fire sprinkler systems, and replace with the following: Exception: Automatic residential fire sprinkler systems shall not be required in townhouses where either two (2) one (1)-hour fire-resistance-rated walls or a common two (2)-hour fire-resistance rated wall, as specified in item number 2 of Section R302.2.2 is installed between dwelling units or when additions or alterations are made to existing townhouses that do not have an automatic residential fire sprinkler system installed. (3-20-20)T

k. Delete Section R313.2 One- and two-family dwellings automatic fire sprinkler systems. (3-20-20)T

l. Delete the exceptions under Section R314.2.2 Alterations, repairs and additions, and replace with the following: Exceptions: 1. Work involving the exterior surfaces of dwellings, such as, but not limited to, replacement of roofing or siding, or the addition or replacement of windows or doors, or the addition of a porch or deck or electrical permits, are exempt from the requirements of this section. 2. Installation, alteration or repairs of plumbing or mechanical systems are exempt from the requirements of this section. (3-20-20)T

m. Delete the exceptions under Section R315.2.2 Alterations, repairs and additions, and replace with the following: Exceptions: 1. Work involving the exterior surfaces of dwellings, such as, but not limited to, replacement of roofing or siding, or the addition or replacement of windows or doors, or the addition of a porch or deck or electrical permits, are exempt from the requirements of this section. 2. Installation, alteration or repairs of noncombustion plumbing or mechanical systems are exempt from the requirements of this section. (3-20-20)T

n. Delete Section R322.1.10 As-built elevation documentation. (3-20-20)T

o. Delete Section R322.2.1 and replace with the following: R322.2.1 Elevation requirements. 1. Buildings and structures in flood hazard areas, including flood hazard areas designated as Coastal A Zones, shall have the lowest floors elevated to or above the base flood elevation. 2. In areas of shallow flooding (AO Zones), buildings and structures shall have the lowest floors (including basement) elevated to a height above the highest adjacent grade

of not less than the depth number specified in feet (mm) on the FIRM, or not less than two (2) feet (610 mm) if a depth number is not specified. 3. Basement floors that are below grade on all sides shall be elevated to or above base flood elevation. Exception: Enclosed areas below the design flood elevation, including basements with floors that are not below grade on all sides, shall meet the requirements of Section R322.2.2. (3-20-20)T

p. Delete subparagraph 2.1 of Section R322.2.2 Enclosed area below design flood elevation, and replace with the following: 2.1. The total net area of all openings shall be at least one (1) square inch (645 mm²) for each square foot (0.093 m²) of enclosed area, or the opening shall be designed and the construction documents shall include a statement that the design and installation of the openings will provide for equalization of hydrostatic flood forces on exterior walls by allowing the automatic entry and exit of floodwaters. (3-20-20)T

q. Delete Tables R403 Minimum Depth (D) and Width (W) of Crushed Stone Footings (inches), R403.1(1) Minimum Width and Thickness for Concrete Footings for Light-Frame Construction (inches), R403.1(2) Minimum Width and Thickness for Concrete Footings for Light-Frame Construction and Brick Veneer (inches), and R403.1(3) Minimum Width and Thickness for Concrete Footings with Cast-In-Place or Fully Grouted Masonry Wall Construction (inches). (3-20-20)T

r. Add the following as Table R403.1:

**TABLE R403.1
MINIMUM WIDTH OF CONCRETE, PRECAST, OR MASONRY FOOTINGS (inches)^a**

	LOAD-BEARING VALUE OF SOIL (psf)			
	1,500	2,000	3,000	≥ 4,000
Conventional light-frame construction				
1-Story	12	12	12	12
2-Story	15	12	12	12
3-Story	23	17	12	12
4-inch brick veneer over light frame or 8-inch hollow concrete masonry				
1-Story	12	12	12	12
2-Story	21	16	12	12
3-Story	32	24	16	12
8-inch solid or fully grouted masonry				
1-Story	16	12	12	12
2-Story	29	21	14	12
3-Story	42	32	21	16

For SI: 1 inch = 25.4 mm, 1 pound per square foot = 0.0479 kPa.

^aWhere minimum footing width is twelve (12) inches, use of a single wythe of solid or fully grouted twelve (12)-inch nominal concrete masonry units is permitted. (3-20-20)T

s. Delete Section R403.1.1 and replace with the following: R403.1.1 Minimum size. Minimum sizes for concrete and masonry footings shall be as set forth in Table R403.1 and Figure R403.1(1). The footing width (W) shall be based on the load bearing value of the soil in accordance with Table R401.4.1. Spread footings shall be at least six (6) inches in thickness (T). Footing projections (P) shall be at least two (2) inches and shall not exceed the thickness of the footing. The size of footings supporting piers and columns shall be based on the tributary load and allowable soil pressure in accordance with Table R401.4.1. Footings for wood foundations shall be in accordance

with the details set forth in Section R403.2 and Figures R403.1(2) and R403.1(3). (3-20-20)T

t. Delete Section R602.10 and replace with the following: R602.10 Wall bracing. Buildings shall be braced in accordance with this Section or, when applicable Section R602.12, or the most current edition of APA System Report SR-102 as an alternate method. Where a building, or portion thereof, does not comply with one (1) or more of the bracing requirements in this Section, those portions shall be designed and constructed in accordance with Section R301.1. (3-20-20)T

03. International Existing Building Code. 2018 Edition. (3-20-20)T

04. International Energy Conservation Code. 2018 Edition with the following amendments: (3-20-20)T

a. Add the following as Section C101.5.2: C101.5.2 Industrial, electronic, and manufacturing equipment. Buildings or portions thereof that are heated or cooled exclusively to maintain the required operating temperature of industrial, electronic, or manufacturing equipment shall be exempt from the provisions of this code. Such buildings or portions thereof shall be separated from connected conditioned space by building thermal envelope assemblies complying with this code. (3-20-20)T

b. Add the following as an exception under Section C402.5 Air leakage—thermal envelope (Mandatory): Exception: For buildings having over fifty thousand (50,000) square feet of conditioned floor area, air leakage testing shall be permitted to be conducted on less than the whole building, provided the following portions of the building are tested and their measured air leakage is area-weighted by the surface areas of the building envelope: 1. The entire floor area of all stories that have any spaces directly under a roof. 2. The entire floor area of all stories that have a building entrance or loading dock. 3. Representative above-grade wall sections of the building totaling at least twenty-five percent (25%) of the above-grade wall area enclosing the remaining conditioned space. Floor area tested under subparagraphs 1. or 2. of this exception shall not be included in the twenty-five percent (25%) of above-grade wall sections tested under this subparagraph. (3-20-20)T

c. Add the following as exception number 7 under Section C403.5 Economizers (Prescriptive): 7. Unusual outdoor air contaminate conditions – Systems where special outside air filtration and treatment for the reduction and treatment of unusual outdoor contaminants, makes an air economizer infeasible. (3-20-20)T

d. Delete Table C404.5.1 and replace with the following:

TABLE C404.5.1 PIPING VOLUME AND MAXIMUM PIPING LENGTHS			
NOMINAL PIPE SIZE (inches)	VOLUME (liquid ounces per foot length)	MAXIMUM PIPING LENGTH (feet)	
		Public lavatory faucets	Other fixtures and appliances
1/4	0.33	31	50
5/16	0.5	N/A - non-standard size	50
3/8	0.75	17	50
1/2	1.5	10	43

TABLE C404.5.1 PIPING VOLUME AND MAXIMUM PIPING LENGTHS			
NOMINAL PIPE SIZE (inches)	VOLUME (liquid ounces per foot length)	MAXIMUM PIPING LENGTH (feet)	
		Public lavatory faucets	Other fixtures and appliances
5/8	2	7	32
3/4	3	5	21
7/8	4	N/A - non-standard size	16
1	5	3	13
1 1/4	8	2	8
1 1/2	11	1	6
2 or larger	18	1	4

For SI: 1 inch = 25.4 mm; 1 foot = 304.8 mm; 1 liquid ounce = 0.030 L; 1 gallon = 128 ounces. (3-20-20)T

e. Delete the rows in Table R402.1.2 for climate zones “5 and Marine 4” and “6” and replace with the following:

TABLE R402.1.2 INSULATION AND FENESTRATION REQUIREMENTS BY COMPONENT ^a										
Climate Zone	Fenestration U- Factor ^b	Skylight U-factor ^b	Glazed Fenestration SHGC ^{b, c}	Ceiling R-Value	Wood Frame Wall R-Value	Mass Wall R-Value ⁱ	Floor R-Value	Basement ^c Wall R-Value	Slab ^d R-Value & Depth	Crawlspace ^c Wall R-Value
5	0.32	0.55	NR	38	20 or 13+5 ^h	13/17	30 ^g	15/19	10, 2 ft	15/19
6	0.30	0.55	NR	49	22 or 13+5 ^h	15/20	30 ^g	15/19	10, 4 ft	15/19

(3-20-20)T

f. Add the following as footnote ^k to the title of Table R402.1.2 - Insulation and Fenestration Requirements by Component: ^k. For residential log home building thermal envelope construction requirements see Section R402.6. (3-20-20)T

g. Delete the rows in Table R402.1.4 for climate zones “5 and Marine 4” and “6” and replace with the following:

TABLE R402.1.4 EQUIVALENT U-FACTORS^a								
Climate Zone	Fenestration U-factor	Skylight U-factor	Ceiling U-factor	Frame Wall U-factor	Mass Wall U-factor^b	Floor U-factor	Basement Wall U-factor	Crawlspace Wall U-factor
5	0.32	0.55	0.030	0.060	0.082	0.033	0.050	0.055
6	0.30	0.55	0.026	0.057	0.060	0.033	0.050	0.055

(3-20-20)T

h. Delete Section R402.4.1 and replace with the following: R402.4.1 Building thermal envelope. 1. Until June 30, 2021, the building thermal envelope shall comply with Sections R402.4.1.1 (Installation) and either Section R402.4.1.2 (Testing) or Section R402.4.1.3 (Visual inspection). 2. Effective July 1, 2021, the building thermal envelope of a minimum of twenty percent (20%) of all new single-family homes constructed by each builder shall comply with Section R402.4.1.1 (Installation) and Section R402.4.1.2 (Testing). The authority having jurisdiction may: 2.1. Determine how to enforce this requirement, starting with the fifth house and continuing with each subsequent fifth house. 2.2. Waive this requirement if significant testing indicates the five (5) air changes per hour (ACH) requirement is consistently being met or exceeded (resulting in a lower ACH). 2.3. Grant exceptions to this requirement in rural areas where testing equipment is not available or cost effective. 3. Effective July 1, 2021, the building thermal envelope of eighty percent (80%) of all new single-family homes constructed by each builder shall comply with Section R402.4.1.1 (Installation) and either Section R402.4.1.2 (Testing) or Section R402.4.1.3 (Visual inspection). 4. The sealing methods between dissimilar materials shall allow for differential expansion and contraction.

(3-20-20)T

i. Delete Section R402.4.1.1 and replace with the following: R402.4.1.1 Installation. The components of the building thermal envelope as listed in Table R402.4.1.1 shall be installed in accordance with the manufacturer’s instructions and the criteria listed in Table R402.4.1.1, as applicable to the method of construction.

(3-20-20)T

j. Delete Section R402.4.1.2 and replace with the following: R402.4.1.2 Testing. Testing building envelope tightness and insulation installation shall be considered acceptable when tested air leakage is less than five (5) air changes per hour (ACH) when tested with a blower door at a pressure of 33.5 psf (50 Pa). Testing shall occur after rough in and after installation of penetrations of the building envelope, including penetrations for utilities, plumbing, electrical, ventilation and combustion appliances. Testing shall be conducted in accordance with RESNET/ICC 380, ASTM E 779 or ASTM E 1827 and reported at a pressure of 0.2-inch w.g. (50 Pascals). During testing: 1. Exterior windows and doors, fireplace and stove doors shall be closed, but not sealed. 2. Dampers shall be closed, but not sealed, including exhaust, intake, makeup air, backdraft and flue dampers. 3. Interior doors shall be open. 4. Exterior openings for continuous ventilation systems and heat recovery ventilators shall be closed and sealed. 5. Heating and cooling system(s) shall be turned off. 6. HVAC ducts shall not be sealed. 7. Supply and return registers shall not be sealed.

(3-20-20)T

k. Add the following as Section R402.4.1.3: R402.4.1.3 Visual inspection. Building envelope tightness and insulation installation shall be considered acceptable when the items listed in Table R402.4.1.1, applicable to the method of construction, are field verified. Where required by code official an approved party independent from the installer of the insulation shall inspect the air barrier and insulation.

(3-20-20)T

l. Add the following as Section R402.6: R402.6 Residential log home thermal envelope. Residential log home construction shall comply with Section R401 (General), Section R402.4 (Air leakage), Section R402.5 (Maximum fenestration U-factor and SHGC), Section R403.1 (Controls), the mandatory sections of Sections R403.3 through R403.9, Section R404 (Electrical Power and Lighting Systems), and either 1., 2., or 3. as follows: 1. Sections R402.2 through R402.3, Section R403.3.1 (Insulation), Section R404.1 (Lightning equipment), and Table R402.6

(Log Home Prescriptive Thermal Envelope Requirements by Component). 2. Section R405 (Simulated Performance Alternative). 3. REScheck (U.S. Department of Energy Building Codes Program). (3-20-20)T

m. Add the following as Table R402.6:

TABLE R402.6 LOG HOME PRESCRIPTIVE THERMAL ENVELOPE REQUIREMENTS BY COMPONENT									
For SI: 1 foot = 304.8 mm.									
Climate Zone	Fenestration U-factor ^a	Skylight U-factor	Glazed Fenestration SHGC	Ceiling R-value	Min. Average Log Size In Inches	Floor R-value	Basement Wall R-value ^d	Slab R-value & Depth ^b	Crawl Space Wall R-value ^d
5, 6 - High efficiency equipment path ^c	0.32	0.60	NR	49	5	30	15/19	10, 4 ft.	10/13
5	0.32	0.60	NR	49	8	30	10/13	10, 2 ft.	10/13
6	0.30	0.60	NR	49	8	30	15/19	10, 4 ft.	10/13

^aThe fenestration U-factor column excludes skylights. The SHGC column applies to all glazed fenestration.

^bR-5 shall be added to the required slab edge R-values for heated slabs.

^c90% AFUE natural gas or propane, 84% AFUE oil, or 15 SEER heat pump heating equipment (zonal electric resistance heating equipment such as electric base board electric resistance heating equipment as the sole source for heating is considered compliant with the high efficiency equipment path).

^d“15/19” means R-15 continuous insulated sheathing on the interior or exterior of the home or R-19 cavity insulation at the interior of the basement wall. “15/19” shall be permitted to be met with R-13 cavity insulation on the interior of the basement wall plus R-5 continuous insulated sheathing on the interior or exterior of the home. “10/13” means R-10 continuous insulated sheathing on the interior or exterior of the home or R-13 cavity insulation at the interior of the basement wall.

(3-20-20)T

n. Delete Section R403.5.3 and replace with the following: R403.5.3 Hot water pipe insulation (Prescriptive). Insulation for hot water piping with a thermal resistance, R-value, of not less than R-3 shall be applied to the following: 1. Piping serving more than one (1) dwelling unit. 2. Piping located outside the conditioned space. 3. Piping located under a floor slab. 4. Buried piping. 5. Supply and return piping in recirculation systems other than demand recirculation systems. (3-20-20)T

o. Delete Section R404.1 and replace with the following: R404.1 Lighting equipment (Mandatory). A minimum of seventy-five percent (75%) of the lamps in permanently installed lighting fixtures shall be high-efficacy lamps or a minimum of seventy-five percent (75%) of the permanently installed lighting fixtures shall contain only high efficacy lamps. (3-20-20)T

p. Delete Section R406.3 and replace with the following: R406.3 Energy Rating Index. The Energy Rating Index (ERI) shall be determined in accordance with RESNET/ICC 301. Energy used to recharge or refuel a vehicle used for transportation on roads that are not on the building site shall not be included in the ERI reference design or the rated design. (3-20-20)T

- q. Delete Table R406.4 and replace with the following:

Table R406.4 - Maximum Energy Rating Index

Climate Zone	Energy Rating Index ^a
5	68
6	68

^a Where on-site renewable energy is included for compliance using the ERI analysis of Section R406.4, the building shall meet the mandatory requirements of Section R406.2, and the building thermal envelope shall be greater than or equal to the levels of efficiency and SHGC in Table R402.1.2 or Table R402.1.4 of the 2015 International Energy Conservation Code. (3-20-20)T

05. References to Other Codes. Where any provisions of the codes that are adopted in this Section make reference to other construction and safety-related model codes or standards which have not been adopted by the involved authority having jurisdiction, to the extent possible, such reference should be construed as pertaining to the equivalent code or standard that has been duly adopted by such jurisdiction. (3-20-20)T

005. -- 025. (RESERVED)

026. DEFINITIONS.

The terms defined in this section have the following meaning for all parts of this chapter, unless the context clearly indicates another meaning: (3-20-20)T

01. Act. The Idaho Building Code Act, Title 39, Chapter 41, Idaho Code. (3-20-20)T

02. Administrator. The administrator of the Division of Building Safety for the state of Idaho. (3-20-20)T

03. Alterations or Conversions of Modular Buildings and Commercial Coaches. Any change from the approved plans or installation instructions which would affect the structural, mechanical, electrical or plumbing systems of modular buildings or commercial coaches bearing a Division insignia of approval and includes the replacement, addition, modification or removal of any structural member, plumbing, heat-producing or electrical equipment, or installation which may affect such systems prior to first occupancy. Any such alteration or conversion shall first be approved by testing and inspection in the same manner as original systems or component parts. The following do not constitute alteration or conversion: (3-20-20)T

a. Repairs with approved replacement parts; (3-20-20)T

b. Conversion of listed fuel-burning appliances in accordance with the terms of their listing; (3-20-20)T

c. Replacement of equipment and appliances in kind; (3-20-20)T

d. Adjustment and maintenance of equipment. (3-20-20)T

04. Alterations to Manufactured Homes. The replacement, addition, and modification, or removal of any equipment or installation after sale by a manufacturer to a dealer but prior to sale by a dealer to a purchaser which may affect the construction, fire safety, occupancy, plumbing, heat-producing or electrical system. It includes any modification made in a manufactured home which may affect the compliance of the home with the standards, but it does not include the repair or replacement of a component or appliance “plug-in” to an electrical receptacle where the replaced item is of the same configuration and rating as the one being replaced. It also does not include the addition of an appliance requiring “plug-in” to an electrical receptacle, which appliance was not provided with the manufactured home by the manufacturer, if the rating of the appliance does not exceed the rating of the receptacle to which it is connected. (3-20-20)T

- Code. **05. Board.** The Idaho Building Code Board created under the provisions of Title 39, Chapter 41, Idaho Code. (3-20-20)T
- 06. Commercial Coach.** In order to further clarify the definition of “commercial coach” as cited in Section 39-4105(5), Idaho Code, the phrase “made so as to be readily movable as a unit on its own running gear” means that the running gear shall be a permanent part of the unit and not intended to be removed or replaced, and such modular structure is used for commercial purposes. (3-20-20)T
- 07. Division.** The Division of Building Safety of the state of Idaho. (3-20-20)T
- 08. Equipment.** All equipment, materials, appliances, devices, fixtures, fittings or accessories installed in the manufacture and assembly of modular buildings. (3-20-20)T
- 09. Field Technical Service.** Interpretation and clarification of the technical data relating to the application of these rules, but not including inspection. (3-20-20)T
- 10. First Purchaser.** The first purchaser of a commercial coach for other than resale. (3-20-20)T
- 11. Insignia.** A label, tab or tag issued by the Division to indicate compliance with the codes, standards, rules and regulations established for manufactured building systems, subsystems, or building elements, modular buildings, and commercial coaches. (3-20-20)T
- 12. Labeled.** Equipment or other building components bearing a label or other approved marking authorized or issued for use by a recognized testing/listing or evaluation agency. (3-20-20)T
- 13. Listed.** Equipment or other building components included within a current list published by a recognized testing/listing agency that maintains periodic inspection on current production of listed equipment or other building components and whose listing states either that the equipment or component complies with recognized standards or has been tested and determined to be suitable for the use intended. (3-20-20)T
- 14. Listing Agency.** A person, firm, association, partnership or corporation which is in the business of listing or labeling and which maintains a periodic inspection program on current production of listed materials, and which makes available, not less frequently than annually, a published report of such listing in which specific information is included that the product has been tested to nationally approved standards and found safe for use in a specified manner. (3-20-20)T
- 15. Minor Alteration.** The following definition is used for the purpose of administering annual permits. (3-20-20)T
- a.** Minor alterations shall include, but are not limited to, the following: partition walls constructed within a defined room; relocation of or existing openings or installation of new doors and windows in non-load bearing walls and not in construction meant to compartmentalize fire; window replacement in unaltered existing openings; roof repairs involving installation of less than one hundred (100) square feet of new roof covering; and new suspended ceilings that are not part of a required fire resistive assembly. (3-20-20)T
- b.** Minor alterations shall not include: work that alters the fire resistive characteristics of the building or fire suppression systems; work that creates new openings in construction meant to compartmentalize fire such as fire walls, fire barriers, fire partitions, smoke barriers, smoke partitions, horizontal assemblies, shaft enclosures, stair enclosures; work that increases the floor area or height of the building; work that changes the structural load path of the building for gravity or horizontal loads; work that reduces the thermal resistant capacity of the building envelop; changes in the occupancy classification of the building or space; increases in the floor loads. (3-20-20)T
- 16. Model.** As referred to in Section 39-4113(3), Idaho Code, for modular buildings and commercial coaches shall mean a specific outside dimension and floor plan with specific structural, plumbing, electrical, and mechanical systems as designated by the manufacturer to be the standard for imitation reproduction. (3-20-20)T

17. **Testing/Listing Agency.** A person, firm, association, partnership or corporation that is: (3-20-20)T
- a. In the business of testing equipment or other building components; and (3-20-20)T
 - b. Recognized by the Division as being qualified and equipped to conduct experimental testing in accordance with recognized standards; and (3-20-20)T
 - c. Not under the jurisdiction or control of any single manufacturer or supplier for an affected industry; and (3-20-20)T
 - d. Making available, not less frequently than annually, a published report in which specific information is included stating that the equipment and systems have been tested and found safe for use in a specified manner. (3-20-20)T

18. **Transit Damage.** Application to manufactured home means that damage encountered en route from the place of manufacture to the dealer or first owner involving structural integrity or any repair that does not result in return to the same construction or assembly as specified in the manufacturer's design approval without additional reinforcement or change. (3-20-20)T

19. **State Buildings.** All buildings to be constructed, altered, or repaired by or for any state of Idaho agency or entity, without regard to purpose, occupancy, or the source of funding for such construction, alteration, or repair. (3-20-20)T

20. **Running Gear.** Springs, spring hangers, axles, bearings, wheels, brakes, rims and tires and their related hardware. (3-20-20)T

21. **Substantially Prefabricated or Assembled.** The module or major portion of modular buildings or commercial coaches assembled in such manner that all portions may not be inspected without disassembly or destruction of the part. (3-20-20)T

22. **Systems Plan.** A design plan concept that allows the interchanging of various approved construction systems to include structural, electrical, plumbing, and mechanical aspects of the system. (3-20-20)T

23. **Technical Service.** Conducting research, evaluation, consultation, model and systems plan reviews, interpretation and clarification by the Division of technical data relating to the application of these rules, and also includes special field inspections that are not covered in other portions of these rules. (3-20-20)T

027. PERMITS.

01. **Building Permits.** Building permits shall be obtained from the Division prior to the construction of structures governed by the act or rules promulgated by the Board. (3-20-20)T

02. **Annual Permit.** In lieu of an individual permit for each minor alteration to an already approved building, the Division may issue an annual permit upon application therefor to any state agency or state governmental organization regularly employing one (1) or more qualified trade persons in the building, structure or on the premises or campus owned or operated by the applicant for the permit. The agency to whom an annual permit is issued shall keep a detailed record of alterations made under such annual permit. The Division shall be allowed access to such records at all times or such records shall be filed with the Division as designated. The permit holder shall request inspections and make the work accessible for inspection as required by the adopted codes and this rule. (3-20-20)T

028. PLAN REVIEW.

01. **Jurisdiction.** The Division shall have exclusive jurisdiction and authority to conduct plan reviews of the construction, additions, repairs, and occupancy of all state buildings of any agency of government at the state level for any purposes or occupancy regardless of the source of funding for such construction, addition, repair, or occupancy. (3-20-20)T

02. Plans Specifications. Construction documents shall be dimensioned and drawn upon suitable material. Plans may be submitted electronically or in digital format as approved by the Division. Drawing format shall be equivalent to the paper format. Construction documents shall be of sufficient clarity to indicate the location, nature, and extent of the work proposed and show in detail that the installations will conform to the provisions of the building code and applicable laws, rules, and policies of the Division. (3-20-20)T

03. Plans Not Required. Plans are not required for group U occupancies of Type V conventional light-frame wood construction. (3-20-20)T

04. Addenda and Change Orders. (3-20-20)T

a. Documents enforcing changes or modifications. Addenda, contract change orders, changes-in-work requests, and other similar written documents enforcing changes or modifications to plans or specifications, already approved by the Division, which addenda, change orders, or change-in-work requests deal with structural or fire resistance changes, or such other changes affecting code conformance, shall be submitted to the Division for approval. The use of the terms “addenda,” “change orders,” and “changes-in-work requests” are not be limited exclusively to such phraseology, but may include such other language used in the professions which essentially have the same meaning. (3-20-20)T

b. Application provisions. The provisions of this Section apply to that work which will be accomplished. (3-20-20)T

029. FEES.
The following fees apply to the functions cited: (3-20-20)T

01. Document Fees. (3-20-20)T

a. Reasonable and suitable fees necessary for copies of any record, plan approval, permit, map, sketch, drawing or other instrument. (3-20-20)T

b. Charges for copies of separate published documents will be actual cost to the Division plus postage. (3-20-20)T

02. Technical Service Fee. One hundred dollars (\$100) per hour. (3-20-20)T

03. Modular Building and Commercial Coaches Fees. Other than as herein specified in this Section, the fee schedule for modular buildings and commercial coaches are as provided herein in Table 1-A, and such fees are based on the Freight On Board (FOB) cost to the dealer at the point of manufacture. (3-20-20)T

04. Insignia Tag Fee. In instances where building permit fees are not charged for modular buildings, a one hundred dollar (\$100) fee will be charged for an insignia. (3-20-20)T

05. Building Permit Fees. The building permit fee for each permit are established in the following table. The determination of value or valuation will be made by the administrator and includes the total value of all construction work for which a permit is issued.

TABLE 1-A - BUILDING PERMIT FEES	
Total Valuation	Fee
\$1 to \$500	= \$23.50
\$501 to \$2,000	= \$23.50 for the first \$500 plus \$3.05 for each additional \$100, or fraction thereof, to and including \$2,000
\$2,001 to \$25,000	= \$69.25 for the first \$2,000 plus \$14 for each additional \$1,000, or fraction thereof, to and including \$25,000

TABLE 1-A - BUILDING PERMIT FEES	
Total Valuation	Fee
\$25,001 to \$50,000	= \$391.75 for the first \$25,000 plus \$10.10 for each additional \$1,000, or fraction thereof, to and including \$50,000
\$50,001 to \$100,000	= \$643.75 for the first \$50,000 plus \$7 for each additional \$1,000, or fraction thereof, to and including \$100,000
\$100,001 to \$500,000	= \$993.75 for the first \$100,000 plus \$5.60 for each additional \$1,000, or fraction thereof, to and including \$500,000
\$500,001 to \$1,000,000	= \$3,233.75 for the first \$500,000 plus \$4.75 for each additional \$1,000, or fraction thereof, to and including \$1,000,000
\$1,000,001 to \$5,000,000	= \$5,608.75 for the first \$1,000,000 plus \$3.65 for each additional \$1,000, or fraction thereof, to and including \$5,000,000
\$5,000,001 to \$10,000,000	= \$20,208.75 for the first \$5,000,000 plus \$2.75 for each additional \$1,000, or fraction thereof, to and including \$10,000,000
\$10,000,001 and up	= \$33,958.75 for the first \$10,000,000 plus \$2 for each additional \$1,000, or fraction thereof

(3-20-20)T

06. Fees for Annual Permits. A fee for inspections performed on annual permits shall be charged at the rate of one hundred dollars (\$100) per hour. The Division shall bill the applicant for annual permits and failure of the applicant to pay the fee within sixty (60) days may result in cancellation of the annual permit. (3-20-20)T

07. Plan Review Fees. Plan review fees shall be charged at an hourly rate of one hundred dollars (\$100) per hour up to a maximum of sixty-five percent (65%) of the calculated building permit fee with a minimum required fee of forty percent (40%) of the calculated building permit fee. All requests for plan review services shall at such time be accompanied by a payment in the amount of at least forty percent (40%) of the calculated building permit fee. Upon completion of the plan review, any additional fees, above the minimum required, are due to the Division by the requesting party. (3-20-20)T

08. Refund of Plan Review Fees. Plan review fees are non-refundable. (3-20-20)T

09. Refund of Permit Fees. The Administrator may authorize a refund of any permit fee paid which was erroneously paid or collected. The Administrator may authorize a refund of not more than eighty percent (80%) of the permit fee paid when no work has been done under a permit issued in accordance with these rules. The Administrator may not authorize a refund of any permit fee paid except upon written application filed by the original applicant not later than one hundred eighty (180) days after the date of permit issuance. (3-20-20)T

030. RIGHT OF ENTRY.

Whenever necessary to make an inspection to enforce any of the provisions of Title 39, Chapters 40 and 41, Idaho Code, or whenever the administrator or his authorized representative has reasonable cause to believe that there exists in any building or upon any premises, any condition which makes such building or premises unsafe, the administrator or his authorized representative shall enter such building or premises at all reasonable times to inspect the same or to perform any duty imposed upon the Division by Title 39, Chapters 40 and 41, Idaho Code; provided that if such building or premises is occupied, he shall first present proper credentials and demand entry; and if such building or premises be unoccupied, he shall first make a reasonable effort to locate the owner or other persons having charge or control of the building or premises and demand entry. If such entry is refused, the administrator shall have recourse to every remedy provided by law to secure entry. (3-20-20)T

031. WORK PROCEEDING WITHOUT PERMIT OR APPROVAL.

Where any work for which a permit or approval, to include plan or system approval, is required by these rules, or by

the codes enumerated in Title 39, Chapter 41, Idaho Code, is started or proceeded prior to obtaining said approval or permit, and after notice to such person doing or causing such work to be done, and such person continues or causes to continue such work, the fees specified in these rules shall be doubled, but the payment of such double fee shall not relieve any persons from fully complying with the requirements of Title 39, Chapters 40 or 41, or both, Idaho Code, or these rules in the execution of the work nor from any other penalties prescribed by law. (3-20-20)T

032. STOP WORK ORDERS.

Whenever any work is being done contrary to any provisions of the codes enumerated in Title 39, Chapters 40 or 41, or both, Idaho Code, or contrary to these rules, the administrator or his authorized representative may order the work stopped by notice in writing to any persons engaged in such work, and any such persons shall forthwith stop such work until authorized by the administrator or his representative to proceed with the work. Stop work orders shall be accompanied by a notice of violation that states the specific violation and code reference. (3-20-20)T

033. PROHIBITED SALE OR OCCUPANCY NOTICE.

Whenever any mobile/manufactured home, commercial coach or other modular building is in violation of any of the provisions of Title 39, Chapter 40 or 41, or both, Idaho Code, or these rules, the administrator may prohibit the sale or occupancy of such building. Prohibited sale or occupancy notices shall be removed only on authority of the administrator or his authorized representative. (3-20-20)T

034. REMOVAL OF ORDERS AND NOTICES; SALE, RENT, LEASE OR OCCUPANCY OF A UNIT BEARING SUCH ORDER OR NOTICE.

Removal of stop work orders, prohibited sale or occupancy notices, or the sale, rent, lease or occupancy of a building or structure, bearing such order or notice by any person not authorized by the administrator or his authorized representative, constitutes a violation under the provisions of Section 39-4126, Idaho Code, and falls under the provisions of Section 18-317, Idaho Code. (3-20-20)T

035. MODULAR BUILDINGS.

01. Alternates and Equivalents. (3-20-20)T

a. Alternatives Acceptable. The provisions of these rules are not intended to prevent the use of alternate designs, materials, appliances, systems, devices, arrangements, or methods of construction not specifically prescribed by Title 39, Chapter 41, Idaho Code, or of these rules; provided, any such alternate has first been recognized by the Division. (3-20-20)T

b. Satisfactory Alternatives. The Division shall recognize any such alternate if it finds that the proposed design is satisfactory and that the material, appliance, device, arrangement, method, system or method of construction is at least the equivalent in performance in quality, strength, effectiveness, fire resistance, durability and adequate for the protection of the health, safety and general welfare of the people of the state of Idaho. (3-20-20)T

c. Unsatisfactory Alternatives. Recognition by the Division shall not be given if there is substantial evidence that any design, material, appliance, device, arrangement, system or method of construction does not conform to the provisions or requirements of prescribed standards or these rules; provided, however, the Division may, in order to substantiate claims for alternates, upon written request cause tests or proof of compliance to be made at the expense of the manufacturer, his agent, or the seller. (3-20-20)T

d. Test Methods. Test methods shall be as specified in the standards of the codes listed in Title 39, Chapter 41, Idaho Code, or by other nationally recognized standards recognized by the Division. If there are no appropriate test methods specified in the standards listed above, the Division shall determine the test procedure. (3-20-20)T

02. Permits. Prior to construction of modular buildings, appropriate building permits shall first be obtained from the Division. (3-20-20)T

03. Plans. (3-20-20)T

a. Specifications for Submittal. Plans shall be submitted in accordance with Subsection 028.03 of

these rules. (3-20-20)T

b. Nonconformance. Should the plan submittal not conform to the requirements of these rules, the applicant shall be notified in writing within fifteen (15) work days of the date they are received by the Division. Should the applicant fail to submit a completely corrected plan submittal in accordance with the information supplied by the Division within ninety (90) days of such notice, the plan submittal will be deemed abandoned and all fees submitted shall be forfeited to the Division. Subsequent submission thereafter shall be processed as a new plan submittal. (3-20-20)T

c. Distribution of Approved Copies. An approved copy of the plan submittal shall be returned to the manufacturer. An approved copy shall be retained at each place of manufacture, and a copy shall be retained by the Division. (3-20-20)T

d. Proprietary Information. All material submitted by the manufacturer in the form of design plans, engineering data, test results, and other design information relating to their application will be considered proprietary information and will not be released for public scrutiny except when so ordered by a court of competent jurisdiction. (3-20-20)T

e. Changes to Approved Modular Building Plans. Where the manufacturer proposes to change his submitted designs or the Division rule is amended to necessitate such a change, the manufacturer shall submit changed plans for examination and approval. (3-20-20)T

04. Inspections. (3-20-20)T

a. Inspections at Manufacturing Plants. The Division shall conduct inspections at the manufacturing plant to determine compliance with the provisions of these rules and with Title 39, Chapter 41, Idaho Code. (3-20-20)T

b. Field Inspection for Alterations and Conversions. Any alteration or conversion of Division approved modular buildings after leaving the manufacturing facility shall be field inspected in accordance with this section by the local unit of government having jurisdiction. (3-20-20)T

c. In-Plant Inspection in Sister States. Where there is evidence that the in-plant inspectional controls in out-of-state plants in states having reciprocal agreements with the state of Idaho are not being maintained for units to be sold or placed in Idaho, the Division reserves the right to make out-of-state inspections, and fees for such inspection as set forth in these rules shall be paid by the manufacturer. (3-20-20)T

05. Insignia. (3-20-20)T

a. Insignia Location. Single units shall have the insignia permanently attached below the electrical service entrance. Multiple section units shall have the insignia permanently attached on all perimeter sections to the outside wall next to the major access opening. For interior units and second story units the insignia shall be permanently attached on the interior wall next to the major access opening. (3-20-20)T

b. Application for Insignia. The manufacturer shall make application for an insignia for each unit to be manufactured as required by Subsection 035.03 of this rule. The permit/insignia application shall be submitted to the Division in accordance with this section and include the appropriate fees. Applications shall include the serial number of each unit for which an insignia is requested. (3-20-20)T

c. Alteration or Conversion. Factory alterations or conversions of an approved modular building prior to first occupancy shall NOT take place until a permit under the provisions of this section has been obtained. The jurisdiction for non-factory produced additions, repairs or alterations to modular buildings and commercial coaches built in conformance with and as prescribed in the Idaho Building Code Act, Section 39-4109, Idaho Code, once such unit has left the manufacturing facility or a dealer's lot, and bears an appropriate insignia of compliance, rests with the local unit of government having the jurisdiction for the administration and enforcement of locally adopted codes prescribed within the Idaho Building Code Act. (3-20-20)T

d. Denial of Insignia. Should inspection reveal that a manufacturer is not manufacturing units according to the codes specified in Title 39, Chapter 41, Idaho Code, and these rules, and such manufacturer after having been served with a notice setting forth in what respect the provisions of the codes or rules have been violated continues to manufacture units in violation of the codes or rules, applications for new insignia shall be denied and insignia issued for units in noncompliance such manufacturer may resubmit an application for insignia. (3-20-20)T

e. Removal of Insignia. In the event any unit bearing an insignia is found to be in violation of the codes enumerated in Title 39, Chapter 41, Idaho Code, or these rules, the Division may remove the insignia and shall furnish the owner or his agent with a written statement of violations. The owner or his agent shall request an inspection after making corrections to bring the unit into compliance before the Division will issue a replacement insignia. (3-20-20)T

f. Serial Number. Each commercial coach rented, leased or sold, or offered for rent, lease or sale in Idaho shall bear a legible identifying serial number in accordance with the provisions of this section and include the state of manufacture. Each section of a multiple modular building shall have the same identifying serial number followed by a numerical sequence identifier and letter suffix. (3-20-20)T

g. Stamp of Serial Number and State of Manufacture. The unit serial number and the state of manufacture shall be stamped into the foremost cross member of all commercial coaches. Letters and numbers shall be three-eighths (3/8) inch minimum height. Numbers shall not be stamped into a hitch assembly or draw bar. The insignia shall be made of etched brass, stainless steel, anodized or alclad aluminum, or other approved material, not less than two hundredths (0.02) inches thick, and three (3) inches by one and three-fourths (1 3/4) inches minimum size, with lettering not less than one-eighth (1/8) inch high. (3-20-20)T

h. Multiple Commercial Coaches. Each section of multiple commercial coaches shall have the same identifying serial number followed by a numerical sequence identifier and letter suffix. (3-20-20)T

i. Data on Insignia. The date of manufacture, showing month, week and year will be shown on the insignia. Such data will be provided by the manufacturer on the application for insignia. (3-20-20)T

036. MANUFACTURED HOMES.

01. Construction and Safety Standards. Effective June 15, 1976, the latest published edition of the Federal Manufactured Home Construction and Safety Standards and Manufactured Home Procedural and Enforcement Regulations shall be in effect for all manufactured homes manufactured within the state of Idaho, and for all new manufactured homes for sale within the state of Idaho. All new manufactured homes offered for sale within Idaho after the effective date of this section shall bear the Housing and Urban Development (H.U.D.) label as authorized in the Federal Manufactured Home procedural and enforcement regulations. Mobile homes manufactured between March 8, 1971 and June 15, 1976 offered for rent, lease, or sale within Idaho shall bear an Idaho insignia of approval. (3-20-20)T

02. Inspections. (3-20-20)T

a. Special Inspection. Whenever there is a transit damage or any alteration made to a certified manufactured home, or both, a special inspection shall be required of any person offering for rent, lease, or sale said manufactured home. The purpose of the inspection is to insure that the repairs or alteration, or both, do not result in the failure of the manufactured home to comply with the standards. (3-20-20)T

b. Installation Inspection. Installation inspections shall be conducted by local jurisdictions in accordance with Title 44, Chapter 22, Idaho Code and the state adopted Idaho Manufactured Home Installation Standard as incorporated by reference in IDAPA 24.39.34, "Rules Governing Manufactured Home Installations," Section 004. (3-20-20)T

03. Fees. (3-20-20)T

a. Payment of Fees. Fees shall be paid to and collected by the Division. (3-20-20)T

b. In-Plant Inspections. The charge for routine in-plant inspections shall be equal to the latest fees approved by the Department of Housing and Urban Development-Office of Manufactured Home Standards: Forty-five dollars (\$45) per floor. (3-20-20)T

c. Other Inspections. For all inspections other than routine whether they be in-plant or in the field (for models produced after June 15, 1976): Seventy dollars (\$70) per hour minimum for inspection and travel time, prorated to the nearest quarter hour, per diem and lodging where applicable, plus the current state rate for mileage, as approved by the State Board of Examiners and listed in the Idaho State Travel Policies and Procedures, Appendix “A,” based on the round-trip distance from point of inspection and the inspector’s office location. (3-20-20)T

037. (RESERVED)

038. INTEGRATED DESIGN AND FUNDAMENTAL COMMISSIONING OF PUBLIC SCHOOL FACILITIES.

01. Definitions. The following definitions are intended to supplement, and should be read in conjunction with the definitions contained in Section 33-356, Idaho Code. (3-20-20)T

a. Fundamental Commissioning. A quality-focused process for enhancing the delivery of a project. It makes use of a qualified third party employed directly by the building owner. (3-20-20)T

b. Integrated Design. Integrated design refers to a collaborative design effort in which each of the individual architectural or engineering professionals focuses on the whole building approach, with an emphasis on optimizing the building’s performance, environmental sustainability, and cost-savings, to include climate, use, loads and systems resulting in a more comfortable and productive environment, and a building that is more energy-efficient than would be realized using current best practices. (3-20-20)T

02. Technical and Educational Information. Technical and educational information related to integrated design and fundamental commissioning in the form of the American Institute of Architects Integrated Project Delivery Guide; Portland Energy Conservation, Inc. (PECI) Commissioning Guides; ASHRAE Guideline 0-2005-The Commissioning Process; and the Northwest Energy Efficiency Alliance Integrated Design Special Focus on Energy Performance Guide is available at the Division office locations including 1090 E. Watertower St., Meridian, Idaho 83642, and 1250 Ironwood Dr., Ste. 220, Coeur d’Alene, Idaho 83814. A building commissioned under the prescriptive approaches defined by any of the above-named national organizations is deemed to have completed the Fundamental Commissioning process. (3-20-20)T

03. Commissioning Agents. The Division has compiled and made available for public examination a list of all known third party building commissioning agents in Idaho and its contiguous states. The Division has ensured that all such commissioning agents appearing on this list have been certified by the Building Commissioning Association (BCA) or other similar certifying entity. (3-20-20)T

04. Annual Optimization Review. (3-20-20)T

a. A public school building that qualifies for the school building replacement value calculation pursuant to Section 33-356(5)(a), Idaho Code, shall undergo an annual optimization review each year following the first year of operations that the involved school district seeks to qualify such building for the building replacement value calculation. (3-20-20)T

b. The systems within a building required to undergo annual optimization review, as well as any relevant measuring criteria for such systems, shall be formulated by the third party commissioning agent that performs the initial fundamental commissioning. The school district shall be provided with a written report from the commissioning agent identifying the systems which will be subject to the annual optimization review along with any other requirements. (3-20-20)T

c. The report required above in Paragraph 038.04.b. of these rules shall include, but is not limited to, at least the following: (3-20-20)T

- i. Verification that the heating, ventilation, and air conditioning (HVAC) controls, dampers, valves, sensors and other equipment used to control the system are functioning as they were at the commissioning of the building. (3-20-20)T
- ii. Verification that the lighting controls are functioning as they were at the commissioning of the building. (3-20-20)T
- iii. The requirement that any changes made to any of the controls contained on the agent’s list after the initial commissioning be re-set back to the commissioned settings unless it can be demonstrated that the new settings result in greater energy efficiency. (3-20-20)T
- d. The annual optimization review shall be performed by persons qualified to make the required determinations and adjustments. (3-20-20)T
- e. The school district shall submit to the Division written verification indicating that the systems identified by the commissioning agent, including those identified in this Section are functioning as they were at the initial commissioning. Such written verification shall also identify the persons performing the optimization and their qualifications. (3-20-20)T

05. Commissioning Anniversary Date. The date upon which the commissioning agent provides the school district with the required written report described in Paragraph 038.04.b. of these rules shall be the commissioning anniversary date for purposes of this Section. If a school district seeks to qualify a building for the building replacement value calculation, the annual optimization review shall be performed within thirty (30) days of the annual commissioning anniversary date following the first year the building is in operation. The written verification required by Paragraph 038.03.e. of these rules is due to the Division not later than sixty (60) days after the annual commissioning anniversary date. (3-20-20)T

06. Fundamental Building Commissioning Requirements. (3-20-20)T

- a. School districts seeking to qualify a building for the building replacement value calculation shall engage a building commissioning agent. (3-20-20)T
- b. The commissioning agent must document the owner’s requirements for each commissioned system in the facility. All HVAC and controls systems, duct work and piping, renewable and alternative technologies, lighting controls and day lighting, waste heat recovery, and any other advanced technologies incorporated in the building must be commissioned. Building envelope systems must also be verified. The owner’s requirements for these systems may include efficiency targets and other performance criteria such as temperature and lighting levels that will define the performance criteria for the functional performance testing that occurs prior to acceptance. (3-20-20)T
- c. The commissioning agent shall include commissioning requirements in the project construction documents. This includes the scope of commissioning for the project, the systems to be commissioned, and the various requirements related to schedule, submittal reviews, testing, training, O & M manuals, and warranty reviews. (3-20-20)T
- d. The commissioning agent shall develop and utilize a commissioning plan. This plan must include an overview of the commissioning process for the project, a list of commissioned systems, primary commissioning participants and their roles, a communication and management plan, an outline of the scope of commissioning tasks, a list of work products, a schedule, and a description of any commissioning testing activities. (3-20-20)T
- e. The commissioning agent must submit a report to the owner once the commissioning plan has been executed. (3-20-20)T

039. -- 999. (RESERVED)

Subject Index

- A**
Adoption & Incorporation By Reference 3
- D**
Definitions, IDAPA 24.39.30 11
Act 11
Administrator 11
Alterations or Conversions of Modular Buildings or Commercial Coaches 11
Alterations to Manufactured Homes 11
Board 12
Commercial Coach 12
Division 12
Equipment 12
Field Technical Service 12
First Purchaser 12
Insignia 12
Labeled 12
Listed 12
Listing Agency 12
Minor Alteration 12
Model 12
Running Gear 13
State Buildings 13
Substantially Prefabricated or Assembled 13
Systems Plan 13
Technical Service 13
Testing/Listing Agency 13
Transit Damage 13
- F**
Fees 14
Building Permit Fees 14
Document Fees 14
Fees for Annual Permits 15
Insignia Tag Fee 14
Modular Building Fees 14
Plan Review Fees 15
Refund of Permit Fees 15
Refund Of Plan Review Fees 15
Technical Service Fee 14
- I**
Integrated Design & Fundamental Commissioning Of Public School Facilities 19
Annual Optimization Review 19
Commissioning Agents 19
Commissioning Anniversary Date 20
Definitions 19
Fundamental Building Commissioning Requirements 20
- Technical & Educational Information 19
- L**
Legal Authority 3
- M**
Manufactured Homes 18
Construction & Safety Standards 18
Fees 18
Inspections 18
Modular Buildings 16
Alternates & Equivalents 16
Insignia 17
Inspections 17
Permits 16
Plans 16
- P**
Permits 13
Annual Permit 13
Building Permits 13
Plan Review 13
Addenda & Change Orders 14
Jurisdiction 13
Plans Not Required 14
Plans Specifications 14
Prohibited Sale Or Occupancy Notice 16
- R**
Removal Of Orders & Notices 16
Right Of Entry 15
- S**
Sale, Rent, Lease Or Occupancy Of A Unit Bearing Such Order Or Notice 16
Stop Work Orders 16
- T**
Title & Scope 3
- W**
Work Proceeding Without Permit Or Approval 15